

V-Gard®200 Industrial Safety Helmets

Non-vented helmet - Functional and stylish



V-Gard 200 Push-Key



V-Gard 200 Fas-Trac III

V-Gard 200 non-vented Safety Helmet

Key features and benefits

- UV stabilised ABS helmet shell offers good resistance to scratches
- Lightweight
- Stylish design
- Short peak for improved upward vision
- Limited rain gutter
- Provides lateral crushing protection
- Standard slots to easily attach MSA visors and/or ear muffs
- 2-or-4 point chinstraps available, including V-Gard universal 4-point chinstrap, chincup in option
- 6 shell colours: white, yellow, red, blue, green, orange
- Options : **MSA LOGO EXPRESS**® pad printing on all helmet sides; retro-reflective stickers; individual naming
- Lifetime: 3 years storage, +5 years service time; MSA delivers stickers to note date of first use and stick to inside shell
- Anti-static assembly; ELECTROSTATIC-INERIS certified for use in ATEX/explosive environments
- 3 suspensions available:
 - Push-Key with slide adjustment and wipeable PVC sewn in sweatband
 - Fas-Trac® III with wheel ratchet and sweat-wicking foam sweatband
 - Fas-Trac® III with wheel ratchet and wipeable PVC sewn in sweatband

V-Gard®200 Industrial Safety Helmets

Non-vented helmet - Functional and stylish



MSA Suspensions - General features and benefits

- Overhead straps made of woven polyester providing high comfort and long term, consistent shock absorption performance
- Ensures consistent performance and comfort level even under the influence of moisture or low temperatures
- Sophisticated 4-point attachment: good positioning, stability and better air circulation
- Ideal positioning of the harness through height and length adjustment: perfect for use with face masks
- Self-adjusting textile crown straps for fast height adjustment and comfortable fit



MSA Push-Key suspension

Features and benefits

- **EASE OF USE:**
 - This is the fastest sliding suspension on the market: simple push to loosen, squeeze to tighten
 - Can be adjusted with one hand even when worn
- **SURE FITTING:**
 - It offers greater retention capacity than competitive sliding suspensions because it's so much easier to select the best adjustment position
- **ADJUSTABILITY:**
 - 2 levels of nape adjustment for fitting comfort
 - Designed to avoid interference with other PPE such as ear muffs
- **SWEATBAND COMFORT:**
 - Sewn in PVC perforated & wipeable sweatband

MSA Fas-Trac® III suspension



Features and benefits

- **BALANCE & STABILITY:**
 - Lower nape strap improves retention: Helmets stay on when leaning over
 - Adjusts for a custom fit to the back of the head
- **HEADBAND COMFORT:**
 - The comfort pad by separating the ratchet from the head, cradles the head increasing comfort and cooling airflow
 - Prevents hair from getting pulled
- **EASE OF USE:**
 - Ratchet offers smooth rotation: reduced effort to turn
 - Easy grip knob adjustable even with gloves on
- **ADJUSTABILITY:**
 - Three levels of nape height adjustment giving superior nape fit
 - Avoids interference with other PPE such as ear muffs
- **SWEATBAND COMFORT:**
 - Largest sweatband surface area on the market covers more of the headband and user's forehead for increased comfort
 - 2 different sweatband options: sewn in PVC perforated wipeable or sweat-wicking washable foam (breathable fabric allows direct air permeation)
 - Replaceable foam sweatband can be attached over the existing sweatband without demounting the suspension

Also available Terry cotton washable sweatband that can be used over both sewn in PVC or replaceable foam sweatbands for increased user comfort



Technical Specifications

| Shell | |
|---|--|
| Shell material | ABS (Acrylonitrile Butadiene Styrene), UV stabilized, Non-Vented |
| Weight | 279g |
| Suspensions | |
| Weight | Push-Key with slide adjustment and wipeable PVC sewn in sweatband: 70 g Fas-Trac® III with wheel ratchet and sweat-wicking foam sweatband: 89 g Fas-Trac® III with wheel ratchet and wipeable PVC sewn in sweatband: 91 g |
| Webbing | Black Polyester (PET), double straps, 4 points |
| Sweatband material | Push-Key with wipeable sewn in PVC sweatband and Polyurethane (PU) internal foam. Nontoxic PVC in contact with the head. Fas-Trac® III with wipeable sewn in PVC sweatband and Polyurethane (PU) internal foam. Nontoxic PVC in contact with the head. Fas-Trac® III with sweat-wicking Polyurethane (PU) internal grey foam and grey Polyamide (PA) finish in contact with the head. Machine or hand washing (max. 50 cycles) |
| Headband | Fas-Trac® III : Polypropylene (PP) Push-Key : Low Density Polyethylene (LDPE) |
| Clips | Grey Polypropylene (PP) |
| Comfort pad (Fas-Trac® III) | Low Density Polyethylene (LDPE) |
| Adjustment | Fas-Trac® III : (Ratchet): Polyoxymethylene (POM), Polypropylene (PP) and Polyamide (PA) Push-Key : (Button) : Polyoxymethylene (POM) |
| Size | 52-64 cm |
| Metal parts | No |
| Approvals | |
| Standard | Certified by European Notified Body DGUV (0299) according to: - EN 397: 2012 - Shock absorption, resistance to penetration, flame resistance, chinstrap anchorage With Options : Very low temperature / -30°C, Electrical insulation / 440 V AC , Lateral Deformation / LD - EN 50365:2002 electrical class 0 nominal voltage up to 1000 V A.C. and 1500 V D.C. The voltage used for this test is 10 000 V. |
|  | |
| Other standards | Certified by INERIS to EN ISO 80079-36 : 2016 & CEI/TS 60079-32 : 2017 for safe use in ATEX areas* (ELECTROSTATIC-INERIS Certificate n° 29406) - Industry: Dust: hazardous zones 20, 21, 22 (all zones) Gas: zones 1 and 2 with gas group IIA (propane) - Mines: any type of extraction and any depth *Caution:when working in an ATEX area operatives must be fully equipped with appropriate PPE eg. dissipative shoes (earth resistance less than 1.108Ω), not just suitable industrial helmets! |
|  | |
| Lifetime guidelines | |
| Storage time (when helmet not used) | 3 years from shell injection date (helmet packed in proper condition, not exposed to light, chemical or any type of pollution). Store in a proper storage bag and/or in a closed cabinet to avoid extended exposure to sunlight, cold, humidity, exhaust fumes, etc. If the helmet has been stored more than 3 years, deduct the extra storage time from the recommended helmet's service life. NB: For EN 50365 class 0 helmets recommended storage temperature 20 ±15 °C to ensure performance |
| Service life (in addition to the storage time) | 5 years from actual starting date of use MSA recommends writing the date of first use onto a sticker (supplied with each helmet) and then sticking into the shell.This is normally the point at which service life starts |
| Suspension (Push-Key and Fas-Trac® III) | Replace when damaged or contaminated , or as required for hygienic reasons |

V-Gard®200 Industrial Safety Helmets

Non-vented helmet - Functional and stylish



Packaging

| Description | |
|--------------------------------|---|
| Individual (sales unit) | One helmet in a protective plastic bag with instructions, 1 tab suspensions fitted or 4 tabs suspensions fitted (GVxxx-xxAxxxx-xxx) |
| Box | Minimum order quantity: 20 helmets Box size: 706x586x455 mm (one tab fitted) or 720x610x460 mm (4 tab fitted) |
| Pallet | 200 helmets (10 boxes of 20 helmets) Pallet size: 1200 x 730 x 1980 mm |

Ordering Information

| Colors | RAL Code | V-Gard 200 NV PK PVC sweatband | V-Gard 200 NV FTIII PVC Sweatband | V-Gard 200 NV FTIII foam sweatband |
|--------|----------|--------------------------------|-----------------------------------|------------------------------------|
| White | RAL 9003 | GV711-000000-000 | GV712-000000-000 | GV719-000000-000 |
| Yellow | RAL 1018 | GV721-000000-000 | GV722-000000-000 | GV729-000000-000 |
| Red | RAL 3020 | GV731-000000-000 | GV732-000000-000 | GV739-000000-000 |
| Green | RAL 6016 | GV741-000000-000 | GV742-000000-000 | GV749-000000-000 |
| Blue | RAL 5003 | GV751-000000-000 | GV752-000000-000 | GV759-000000-000 |
| Orange | RAL 2008 | GV761-000000-000 | GV762-000000-000 | GV769-000000-000 |

| Part No. | Description | ATO digit when fitted to helmets |
|----------|--|----------------------------------|
| 10162752 | Fas-Trac® III suspension with ratchet and sewn in PVC sweatband | GVxx2 |
| 10162755 | Fas-Trac® III suspension with ratchet and replaceable, washable, foam sweatband | GVxx9 |
| 10162507 | Push-Key suspension with slide adjustment and sewn in PVC sweatband | GVxx1 |
| 10153518 | Fas-Trac® III foam sweatband (10 pcs) – replacements for 10162755 or GVxx9 or over | |
| 696688 | Terry cotton (Terri-Band) sweatband (10 pcs) – for use over sewn in PVC sweatband | |



| Other accessories and options | Ask for our detailed data-sheets |
|-------------------------------|--|
| Options | Lamp brackets |
| Options | MSA LOGO EXPRESS® pad printing on all helmet sides |
| Accessories or Options | Chinstraps |
| Accessories or Options | High visibility stickers |
| Accessories | Helmet mounted ear-muffs |
| Accessories | Individual naming |
| Accessories | Frame and visors |
| Accessories | Winter liners |
| Accessories | Cooling liners |
| Accessories | Neck curtains |



Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice. MSA is a registered trademark of MSA Technology, LLC in the US, Europe, and other Countries. For all other trademarks visit <https://us.msasafety.com/Trademarks>.