


<b>NAME:</b> <b><u>LYNX GREEN</u></b>	
<b>REFERENCE:</b> <b><u>1257.56</u></b>	
<b>FAMILY:</b> <b><u>II</u></b>	

PRODUCT DESCRIPTION	
<b>CERTIFICATION NORM:</b> <b><u>EN ISO 20345:2011</u></b> <b>Additional requirement: <u>IEC 61340-4-3</u></b>	<b>PROTECTION CATEGORY:</b> <b><u>S3 SRC</u></b> <b><u>ESD</u></b>
<b>PROTECTION TOECAP:</b> <b><u>COMPOSITE (resistant at impact 200J and compression 15kN)</u></b>	<b>PROTECTION INSERT:</b> <b><u>KEVLAR (penetration resistant at 1100N)</u></b>
<b>SIZES:</b> <b><u>39 to 47</u></b>	<b>COLOUR:</b> <b><u>BLACK/GREEN</u></b>
<b>UPPER RAW MATERIALS:</b> <b><u>UPPER: WR BREATHABLE HI-TECH MF</u></b>	<b>LINING MATERIALS:</b> <b><u>DRYTEX PLUS GREEN</u></b>
<b>OUTSOLE:</b> <b><u>Direct injected double density PU</u></b>	<b>INSOCK:</b> <b><u>LAVORO ANTISTATIC</u></b>
<b>OTHER CHARACTERISTICS:</b> <ul style="list-style-type: none"> <li>▪ Direct Injected double density PU outsole: anti vibration, antistatic, lateral stability, resistance at hydrolysis, resistance to fuel oil, energy absorption on seat region;</li> <li>▪ Electric Static Discharge (ESD) – IEC 61340-4-3</li> <li>▪ DRYTEX PLUS - Textile absorbing lining;</li> <li>▪ 100% Metal Free</li> <li>▪ 100% Leather Free</li> <li>▪ Use for: all year</li> </ul>	
<b>PRODUCT APLICATIONS:</b> OUTDOOR <input checked="" type="checkbox"/> <b><u>Transport and distribution; Engineering</u></b> INDOOR <input checked="" type="checkbox"/> <b><u>Electronic Industry; Warehouse</u></b> SPECIALS <input type="checkbox"/> _____	