

FIRECHIEF LAYFLAT HOSES

FIRECHIEF[®]
making the world a safer place

MODEL:

LH65/23/2

LH65/23/3



LH65/23
103-1088



LH65/23/3
103-1089

- Layflat hoses conform to respective requirements of BS6391:2009:
Type 2 - LH65/23
Type 3 - LH65/23/3
- Complete with light alloy instantaneous couplings
- Type 2 is constructed from close woven twill polyester filament yarns with synthetic rubber lining
- Type 3 has a premium nitrile rubber outer jacket
- No drying
- Quick to stow
- Designed for emergency use



FIRECHIEF LAYFLAT HOSES



Durable hosing:

LH65/23/2 (Type 2) manufactured from close woven twill polyester filament yarns with synthetic rubber lining.

LH65/23/3 (Type 3) incorporates a premium nitrile rubber outer jacket.

MODEL:

LH65/23/2

LH65/23/3



Model	LH65/23/2	LH65/23/3
Product Code	103-1088	103-1089
Storage Height (approx) (mm)	120	100
Storage Diameter (approx) (mm)	420	440
Weight (kg)	14.1	15
Overall length (m)	23	23
Internal diameter (mm)	65	65
Working Pressure (bar)	15	15
Burst Pressure (bar)	50	50
Unit of Sale	1	1

All hoses supplied with 2.5" instantaneous couplings in aluminium alloy.