

Product data sheet

uvex pronamic alpine/ uvex pronamic alpine Mips



Product characteristics:

- Multi-standard helmet that meets the requirements of EN 397 and EN 12492
- Patented MIPS inner shell available as an option
- Side Euroslot adapters (30 mm) for attaching earmuffs
- Four retaining clips for fitting head torches or goggles
- Additional elements allow our wide range of accessories to be attached to the helmet
- Air vents for maximum ventilation
- Closed helmet shell for work in low-voltage areas (uvex pronamic alpine E)
- Maximum field of vision due to design-optimized brim geometry
- Versatile and adjustable suspension harness with stepless wheel ratchet system
- EPS inner shell ensures excellent fit and comfort
- EN 12492 forked chin strap (art. no. 9790351) included in the standard scope of delivery, EN 397 version (art. no. 9790021) sold separately as an accessory
- replaceable hygiene kits 9790350 and 9790352 (MIPS)

Standards and requirements:

The uvex pronamic alpine series meets the requirements of Regulation 2016/425 and is CE marked.

They meet the harmonized standards EN 12492:2012 (uvex pronamic alpine E: except requirement 4.1.4 ventilation), EN 50365:2002 (uvex pronamic alpine E) and EN 397:2012+A1:2012 as well as their optional requirements MM (Molten Meltal), LD (increased lateral stiffness) and low temperatures (-30°C).

In addition, the products also meet the requirements according to UKCA.

This PPE is subject to the conformity assessment procedure and is monitored by:

CE:

PZT GmbH, Bismarckstraße 264 B,
26389 Wilhelmshaven, Germany
(notified body number 1974)

UKCA:

SATRA
Wyndham Way
Telford Way Industrial Estate
Kettering NN16 8SD
UNITED KINGDOM
(notified body number 0321)

The applicable jurisdiction can be found on the Declaration of Conformity.

You can find this under: uvex-safety.com/ce or

uvex-safety.co.uk/en/media/ukdeclarations-of-conformity/

Technical data:

Sizes:	51 to 63cm
Interior:	EPS-Inner shell/ MIPS-Inner shell
Weight:	505g (Standard)/ 535g (MIPS)

Materials:

Helmet shell:	ABS
Interior:	EPS
Headband:	PP
Sweatband:	Plastic
Padding:	Plastic

Use and storage:

Operating temperature:	-30 °C to +50 °C
Operating time:	4 years from the date of first use
Recommended storage conditions:	Store helmet dry (room temperature) and out of sunlight
Storage time:	4 years from the date of production

Variants/colors:

Article-Nr.	Designation	Color	Packaging unit
9735030	uvex pronamic alpine white	white	1 piece
9735130	uvex pronamic alpine hi-viz yellow	hi-viz yellow	1 piece
9735134	uvex pronamic alpine yellow	yellow	1 piece
9735230	uvex pronamic alpine hi-viz orange	hi-viz orange	1 piece
9735330	uvex pronamic alpine red	red	1 piece
9735430	uvex pronamic alpine green	green	1 piece
9735530	uvex pronamic alpine blue	blue	1 piece
9735930	uvex pronamic alpine black	black	1 piece
9735031	pronamic alpine MIPS white	white	1 piece
9735131	pronamic alpine MIPS hi-viz yellow	hi-viz yellow	1 piece
9735231	pronamic alpine MIPS hi-viz orange	hi-viz orange	1 piece

uvex pronamic alpine E

Article-Nr.	Designation	Color	Packaging unit
9736030	uvex pronamic alpine E white	white	1 piece
9736130	uvex pronamic alpine E hi-viz yellow	hi-viz yellow	1 piece
9736230	uvex pronamic alpine E hi-viz orange	hi-viz orange	1 piece
9736031	pronamic alpine E MIPS white	white	1 piece
9736131	pronamic alpine E MIPS hi-viz yellow	hi-viz yellow	1 piece
9736231	pronamic alpine E MIPS hi-viz orange	hi-viz orange	1 piece

Accessories:

Article-Nr.	Designation	Packaging unit
9790350	Hygiene set pronamic alpine	1 set
9790351	Chin strap EN 12492 pronamic alpine	1 piece
9790352	MIPS hygiene set pronamic alpine	1 set
9790353	Comfort pad pronamic alpine	1 piece
9790021	Chin strap EN 397	1 piece
9790022	Chin strap-Clip	1 piece
	All uvex hearing protection solutions with helmet connection	
	Visors which are specified for the pronamic alpine	
	All helmet lamps from the uvex range	