



# Cushion Link Solid Top - 100% Nitrile

Cushion Link Solid Top is a modular anti-fatigue matting system. The textured surface provides outstanding ergonomic comfort and safety in heavy duty dry or wet industrial areas. Manufactured from the highest quality resilient rubber compounds, Cushion Link Solid Top - 100% Nitrile is resistant to extreme temperatures, oils, coolants and most chemicals. The adaptable solid top design is also compatible with our Cushion Link Open Top range.

All Cushion Link mats can be interlocked and edged using a simple bevel system to create any size or shape, whilst the unique interlocking mechanism along with male and female edges and bevels, provide secure connectivity. This product is also compatible with our Cushion Link Open Top range.

## Features

- ◆ **Typical applications:** Perfect for oily, greasy, welding and manufacturing areas.
- ◆ **Material:** Nitrile rubber.
- ◆ **Cleaning:** Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended.
- ◆ **Sustainability:** Nature friendly, biodegradable and recyclable. REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- ◆ **Warranty:** Lifetime.



Black only. Bevels available in both black and yellow



For more information about this product or, to place an order [click here](#)



Code	Metric	Imperial	Thickness	Weight	Type	Colour
CLS36NFR	92cm x 92cm	3' x 3'	19mm	10.2kg	Mat	Black
CLS36BBF	92cm x 5.5cm	3' x 2"	19mm	0.75kg	Bevel - Female	Black
CLS36BBM	92cm x 5.5cm	3' x 2"	19mm	0.90kg	Bevel - Male	Black
CLS36YBF	92cm x 5.5cm	3' x 2"	19mm	0.75kg	Bevel - Female	Yellow
CLS36YBM	92cm x 5.5cm	3' x 2"	19mm	0.90kg	Bevel - Male	Yellow

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

## Our delivery promise

We guarantee your order will be shipped on time, every time.  
That's the Blue Diamond difference.

# Cushion Link Solid Top - 100% Nitrile

## Technical Specification

Slip resistant:	Excellent slip resistance to level 3. Our abrasive product is recommended for extremely slippery areas (slip resistant to R13 according to DIN51130)
Anti-fatigue:	Excellent anti-fatigue properties, resistant to level 3
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall
Chemical resistant:	Yes
Connectable:	Yes, the mats are modular and interlocking with bevelled edges to create ramps to all sides
Cut to size:	Yes, mat can be cut to bespoke sizes
Disability friendly:	Yes, the mats have ramped edges making them suitable for wheelchair users
Dry area:	Yes
Oily and greasy area:	Yes
Heavy area:	Yes
Welding area:	Yes
Wheeled area:	Yes
Environment:	Suitable for indoor and outdoor use
Flame retardant:	Yes
Impact resistant:	Yes
Product testing:	<ul style="list-style-type: none"> <li>◆ Tensile strength: 3-3.5 Mpa</li> <li>◆ Hardness: 55+ Shore A</li> <li>◆ DIN abrasion loss mm<sup>3</sup>: 250-300</li> <li>◆ Elongation at break: 200-250%</li> <li>◆ Fire tested to: BS EN 13501-1 Class Efl – S2</li> </ul>
Sustainability:	<ul style="list-style-type: none"> <li>◆ Nature friendly, biodegradable and recyclable</li> <li>◆ REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)</li> <li>◆ Contributes to a cleaner environment by reducing the need to use cleaning chemicals</li> </ul>
Temperature resistance:	-20°C to +130°C
Cleaning:	Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended