



# 110V ELECTRIC AIRDECK INFLATOR/ 220V ELECTRIC AIRDECK INFLATOR

PRODUCT NO: SS1101AD (110V) / SS1103AD (220V)

## PRODUCT DESCRIPTION:

Air Pressure : 5.7 kPa  
Maximum air volume: 4.1 m<sup>3</sup>/ minute  
No load speed: 16.000 min  
Overall length: 479mm  
Net weight: 2.0kg  
Vibration emission: (ah) 2.5m/s<sup>2</sup>  
Sound level: (Lwa) 94dB  
Power source: 110v 50-60Hz/220v-240v 50Hz

## MATERIAL SPECIFICATION:

Double insulated plastic casing  
Copper wire  
EPDM Rubber inflation and suction nozzle

## OPERATING AND DESIGN STANDARDS:

Conforms to 2006/42/EC  
Manufactured to EN60745  
Vibration determined to EN60745  
Weight according to EPTA 01/2003

## INSPECTION ROUTINE:

### Before each work session

Always be sure the tool is switched off and unplugged before inspection is performed.  
Visually inspect cable and plug connection.



110V MODEL SHOWN

## MAINTENANCE SCHEDULE:

### Every 3 months

Keep all parts clean and dust free.  
Do not use any solvents to clean only a dry rag.  
PAT testing to be carried out by authorised and competent person.  
Spare parts available from Sayfa Systems.

## TRAINING REQUIREMENTS:

All operatives must be trained and wear appropriate PPE including gloves, goggles and ear protection.  
Sayfa Systems offer product training and operator certification.