

RECHARGEABLE

INTRINSICALLY SAFE DUAL-LIGHT™ FLASHLIGHT

XPR-5542GMX

**NIGHTSTICK**®  
Life Depends on Light™



## DUAL-LIGHT™

**275-lumen** Dual-Light™ provides simultaneous **flashlight and floodlight** operation

**400 LUMENS**



Large, textured buttons that are **easy-to-use with gloves**



Durable polymer body is **impact & chemical resistant**



**Non-conductive body** designed for hazardous environments



**Powerful base magnet** allows "hands-free" use



# DUAL-LIGHT™ FLASHLIGHT

## RECHARGEABLE

### ITEM NUMBER/UPC

XPR-5542GMX - 017398806008

### CERTIFICATIONS

- cULus
- ATEX
- IECEX
- Kosha
- CE
- BC

### CASE MATERIAL

- ABS Polymer

### LUMENS/RUNTIME

#### SPOTLIGHT

- HIGH: 400 lumens, 10 hrs runtime

#### FLOODLIGHT

- HIGH: 225 lumens, 11 hrs runtime

#### DUAL-LIGHT

- 275 lumens, 10 hrs runtime

### CANDELA

- HIGH: 11571

### BEAM DISTANCE

- HIGH: 215m

### WATER RATING

- IP-67 (dust-proof/waterproof)

### DROP RATING

- 2m

### DIMENSIONS

- LENGTH: 9.5 in (241 mm)
- BARREL DIAMETER: 1.2 in (30 mm)
- BEZEL DIAMETER: 1.6 in (40 mm)
- WEIGHT: 10.9 oz (309 g)

### BATTERY

- Integrated li-ion battery

### WARRANTY

- Limited lifetime warranty

### WHAT'S INCLUDED

- Light with li-ion rechargeable battery
- Snap-In rapid charger
- AC/DC power supplies
- Anti-roll ring
- Instruction manual

FL 1 STANDARD	FLASH HIGH	FLASH LOW	DUAL-LIGHT
	400 LUMENS	80 LUMENS	275 LUMENS
	10h	41h	10h
	215m		
	11571cd		

**Bayco Products, Inc.**  
Wylie, TX 75098  
**XPR-5542**

Ex ia FLASHLIGHT FOR USE IN  
HAZARDOUS LOCATIONS

UL listed for use with Bayco Li-ion Battery  
Pack 5500-BATT

**UL** **US**  
LISTED  
E 467756  
ID 5012927  
INTRINSICALLY SAFE  
SECURITE INTRINSEQUE

**CE** 2575  
ZZ-AV480-0248X

**Ks**

CLASS I DIV 1 GRPS A-D T4  
CLASS II & III DIV 1 GRPS E-G  
CLASS I ZONE 0 GRP IIC T4  
CLASS II ZONE 20 IIC T135°C  
Ex ia IIC T4 Gb  
Ex ia IIC T4 Gb  
DEMKO 16 ATEX 1815  
IECEX UL 16.0168  
-20°C ≤ Tamb ≤ +40°C  
3.7V/Cell 5500-BATT  
U<sub>n</sub> = 4.75V

SEE INSTRUCTION MANUAL  
VOIR MANUEL

US Patent 9.713.217 MFG MM-YY

**CERTIFIED**

**UL** **US**  
LISTED

**Ex**

**IECEX**

**CE**

**BC**

**Ks**