

**Product Datasheet uvex i-3 add 1.0**  
**Material No. 6108.210****UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth**

<b>Productcharacteristic</b>	<ul style="list-style-type: none"><li>• innovative spectacle with invisible integrated dioptre correction for near vision, +1,0 dpt.</li><li>• patented lens technology</li><li>• free-form lens design, manufactured in accordance with standard parameters and designed for a distance of approx. 64 mm between the eyes</li><li>• extremely good coverage and fit all the way to the side area</li><li>• individually adjustable side arms with variable inclination</li><li>• integrated Softflex zone ensures outstanding wearer comfort for all head sizes</li><li>• Softflex adjustable nose piece ensures comfortable, pressure-free fit and remain firmly in place</li></ul>
<b>Technical details</b>	
<b>Frame</b>	
Material	TPU/TPE
Features	Variable inclination, individually adjustable
Colour	anthracite, lime
	<b>Marking</b>

Manufacturer	W
EN Standard	166
Low-energy impact	F (45 m/sec) EN 166
Resistance to high speed particles at extremes of temperat.	T
Conformity symbol	CE
<b>Lens</b>	
Material	PC
Coating	supravision HC-AF
Colour	clear
Feature	integrated dioptrre correction; +1,0 dpt.
<b>Marking</b>	
Filter	2C-1,2 (DIN EN 170)
Manufacturer	W
Optical class	1
Low-energy impact	F (45 m/sec)
Resistance to high speed particles at extremes of temperature	T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
Corr./PD	i-3 add 1.0, PD 64 / Add. 1,0 dpt.
<b>Miscellaneous</b>	
Weight	38g
Packing	1 piece in soft spectacles case with microfiber cloth
Standards	DIN EN 166 + DIN EN 170