



DATA SHEET

ProSolve Gaffa Tape (GAFT)

Product Description

A heavy-duty tape, used for bonding, sealing, joining and light to heavy duty packaging.

Features

- PE coated cloth mesh
- Synthetic rubber adhesive with high tack, peel, and shear
- Easy to apply on variety of surfaces

Typical Physical Properties

		Test Method
Backing	PE Coated Cotton Mesh	N.A.
Adhesive	Synthetic Rubber	N.A.
Total Thickness	130 mic +/- 5%	D3652
Tensile Strength	>30 N/25mm	D3759
Elongation	12%	D3759
Adhesion To Steel	>1000 N/25mm	D3330
Shear	>24 hours	D3654
Service Temperature	-20°C ~ + 60°C	N.A.

Storage & Shelf Life:

12 months when stored at $23 \pm 2^{\circ}\text{C}$ (73°F) / 50% relative humidity out of direct sunlight.

Surface Preparation:

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, free of grease, oil or other contaminants.

IMPORTANT NOTICE

All statements, technical information and recommendations are based on tests we believe to be reliable as at the date of hereof, but the accuracy or completeness thereof is not guaranteed. Please ensure before using the product that it is suitable for your intended use. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, other than for fraudulent misrepresentation, ProSolve expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

BEFORE USE, CONSULT THE DATA SHEET OF THE PRODUCT.