

Neoprene cuff with Velcro[®] closure for a secure fit

Back-of-hand knuckle padding for incidental bumps/impact

Form-fitting, quality materials

Layering of SuperFabric[®]* brand materials provide industry-leading cut and needlestick resistance (interior layer) and high pressure fluid resistance – fluid injection resistant up to 700 bar (10150 PSI)

Silicone pattern palm grip

Reinforced fingertips

Launderable

4041 PointGuard[®] Ultra

PROTECTION ZONES:

 3 Layers SuperFabric[®] Protection	 SuperFabric[®] Protection Zone												
	<table border="1"> <tr> <td>ANSI/ISEA CUT</td> <td>GRAM SCORE</td> </tr> <tr> <td>A9</td> <td>6679</td> </tr> <tr> <td>NEEDLESTICK</td> <td>NEWTONS</td> </tr> <tr> <td>LEVEL 5</td> <td>11.546</td> </tr> <tr> <td>EN388: 2016</td> <td>ANSI/ISEA PUNCTURE</td> </tr> <tr> <td>CE </td> <td>4X42F 3</td> </tr> </table>	ANSI/ISEA CUT	GRAM SCORE	A9	6679	NEEDLESTICK	NEWTONS	LEVEL 5	11.546	EN388: 2016	ANSI/ISEA PUNCTURE	CE 	4X42F 3
ANSI/ISEA CUT	GRAM SCORE												
A9	6679												
NEEDLESTICK	NEWTONS												
LEVEL 5	11.546												
EN388: 2016	ANSI/ISEA PUNCTURE												
CE 	4X42F 3												

FEATURES:

HexArmor[®] sets the industry standard for needle protection with solutions for a variety of applications. Our needlestick-resistant products do more than pass industry-accepted testing methods; we put them through real-world applications countless times, with a history of undeniable success. The accepted standards of testing do not account for the many variables employees face on the jobsite, so we created our own tests, mirroring the conditions and hazards that our users face.

ATTRIBUTES:

Style:	Needlestick-resistant
Grip:	Dry or light oil
Cuff Style:	Neoprene with Velcro [®]
Sizes:	6/XS through 11/XXL

HexArmor[®]

HexArmor[®] products are cut and puncture resistant, NOT CUT AND PUNCTURE PROOF. Do not use with moving or serrated blades or tools. Product is fluid injection resistant, NOT FLUID INJECTION PROOF. User shall be exclusively responsible to assess the suitability of the product as specified for any individual application or use. Protection zones are to be used as a general guide. Actual product protection zones may differ. Product features, design, protection zones subject to change.

Protected by patents and patents pending

*SuperFabric[®] is a registered Trademark of HDM, Inc.