

## Product Datasheet uvex 2 6502.1-4 S3 SRC

**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth****Product information**

- Sporty, multifunctional safety shoes
- Extremely light and flexible
- The latest generation of 100% metal-free uvex xenova® toe cap. Compact design, anatomical shape, good side and ankle twist stability, no thermal conductivity and antimagnetic properties
- Metal-free, penetration-resistance insole in accordance with the latest standard, which does not impact shoe flexibility
- Made with new high-performance technology for exceptional wearer comfort
- uvex climazone technology for optimum comfort
- Water-repellent, breathable and extremely soft leather upper
- Distance mesh lining provides optimum breathability
- Individually adjustable due to elastic laces with quick-lock mechanism; normal laces also provided (6502 only)
- Virtually seam-free construction to eliminate pressure points
- Removable comfort insole, antistatic, with moisture control system and additional shock absorption in the heel and at the front of the foot
- Soft, padded collar and padded tongue
- Injection-moulded polyurethane scuffcap to protect upper leather on toe cap and significantly extend resistance time

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |          |        |    |    |    |       |    |    |    |    |          |                          |  |  |  |      |         |  |  |  |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|--------|----|----|----|-------|----|----|----|----|----------|--------------------------|--|--|--|------|---------|--|--|--|
|                       | <ul style="list-style-type: none"> <li>Meets ESD requirements: resistance to ground &lt; 35 megaohm</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |          |        |    |    |    |       |    |    |    |    |          |                          |  |  |  |      |         |  |  |  |
| <b>Outsole</b>        | <ul style="list-style-type: none"> <li>Lightweight two-layer insole with excellent shock absorption characteristics and outstanding slip resistance, free of lacquer wetting inhibitors such as silicones and phthalates (plasticisers)</li> <li>Multilayer shock absorption system comprising double-layer uvex 2 PU outsole and comfortable insole, shock absorption in the front and heel: all this protects the musculoskeletal system, even over long periods of time</li> <li>Optimised ankle protection to ensure safety when working on ladders</li> <li>Particularly abrasion-resistant TPU sections ensure secure stepping and rolling of foot, which helps prevent accidents</li> <li>Rugged, self-cleaning sole ridges ensures maximum grip for demanding applications on uneven or dirty floors (SRC labelling).</li> </ul> |          |        |    |    |    |       |    |    |    |    |          |                          |  |  |  |      |         |  |  |  |
| <b>Technical data</b> | <table> <tr> <td>Art.-no.</td> <td>6502.1</td> <td>.2</td> <td>.3</td> <td>.4</td> </tr> <tr> <td>Width</td> <td>10</td> <td>11</td> <td>12</td> <td>14</td> </tr> <tr> <td>Standard</td> <td colspan="4">EN ISO 20345:2011 S3 SRC</td> </tr> <tr> <td>Size</td> <td colspan="4">35 – 52</td> </tr> </table>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Art.-no. | 6502.1 | .2 | .3 | .4 | Width | 10 | 11 | 12 | 14 | Standard | EN ISO 20345:2011 S3 SRC |  |  |  | Size | 35 – 52 |  |  |  |
| Art.-no.              | 6502.1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | .2       | .3     | .4 |    |    |       |    |    |    |    |          |                          |  |  |  |      |         |  |  |  |
| Width                 | 10                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 11       | 12     | 14 |    |    |       |    |    |    |    |          |                          |  |  |  |      |         |  |  |  |
| Standard              | EN ISO 20345:2011 S3 SRC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |          |        |    |    |    |       |    |    |    |    |          |                          |  |  |  |      |         |  |  |  |
| Size                  | 35 – 52                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |          |        |    |    |    |       |    |    |    |    |          |                          |  |  |  |      |         |  |  |  |
| <b>Accessories</b>    | <p><i>uvex 1 comfortable climatic insole</i><br/>(article no.: 9534.7-9 + .0)</p> <ul style="list-style-type: none"> <li>Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones</li> <li>Ultra breathable and moisture-absorbing materials</li> <li>Shock absorption zones that assist natural movement</li> <li>Non-irritating, comfortable surface structure</li> </ul> <p><i>Laces</i></p> <ul style="list-style-type: none"> <li>Black (article no.: 9599.9 11)</li> <li>Elastic laces (article no.: 9591.000)</li> </ul>                                                                                                                                                                                                                                                        |          |        |    |    |    |       |    |    |    |    |          |                          |  |  |  |      |         |  |  |  |