

LI-ION RECHARGEABLE

VIRIBUS™ INTRINSICALLY SAFE DUAL-LIGHT LANTERN

XPR-5580R

XPR-5580G

**NIGHTSTICK**  
Life Depends on Light™




**Rear green safety lights** provide visibility in smoke filled applications. Includes one Li-ion battery (expandable to 3).



**Carry strap with seat belt style buckle** for additional hands-free use and safety.



**Convenient locking snap-in charger** included.



Sealed switches and body for **dustproof/waterproof (IP-67)** rating, as well as chemical/heat resistant for any environment.

**DUAL  
LIGHT  
TECHNOLOGY**



**300 LUMENS  
DUAL-LIGHT**

HIGH, MEDIUM & LOW SPOTLIGHT  
HIGH, MEDIUM & LOW FLOODLIGHT

**ZONE 0**

**CLASS I  
DIV 1**

**IT FLOATS**



AVAILABLE IN MULTIPLE COLORS.



| FL1 STANDARD | FLASH HIGH | FLASH LOW | DUAL-LIGHT |
|--------------|------------|-----------|------------|
|              | 210 LUMENS | 30 LUMENS | 300 LUMENS |
|              | 12h        | 65h       | 9h 15min   |
|              | 635m       |           |            |
|              | 101000cd   |           |            |
|              | 2m         |           |            |
|              | 1m         |           |            |

**210 LUMENS**

**VIRIBUS™**

# DUAL-LIGHT LANTERN

## LI-ION RECHARGEABLE

### ITEM NUMBER/UPC

XPR-5580G, UPC# 017398805957  
XPR-5580R, UPC# 017398805964

### MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

### CERTIFICATIONS

- cULus, ATEX, IECEx, CE, UKCA, Meets requirements of NFPA-1971-8.6 (2016), Charger meets requirements of NFPA-1901 (2013) Mounted in any Position

### CASE MATERIAL

- Engineered polymer

### LUMENS/RUNTIME

#### FLASHLIGHT

- HIGH: 210L, 12.5 hrs. runtime
- MEDIUM: 100L, 19.5 hrs. runtime
- LOW: 30L, 65 hrs. runtime

#### FLOODLIGHT

- HIGH: 200L, 14 hrs. runtime
- MEDIUM: 100L, 19 hrs. runtime
- LOW: 30L, 65 hrs. runtime

#### DUAL-LIGHT

- 300L, 9.25 hrs. runtime

### CANDELA

#### FLASHLIGHT

- HIGH: 101,000
- MEDIUM: 16,515
- LOW: 6,705

### BEAM DISTANCE

#### FLASHLIGHT

- HIGH: 635m
- MEDIUM: 257m
- LOW: 164m

### WATER RATING

- IP-67 (dustproof and waterproof)

### DROP RATING

- 2 meters

### DIMENSIONS

- LENGTH: 8.25 in (210mm)
- WIDTH: 3.6 in (91mm)
- DEPTH: 5.5 in (140mm)
- BEZEL DIAMETER: 4.7 in (118mm)
- WEIGHT: 2 lbs. 1oz. / 936 g

### BATTERY

- Rechargeable Li-ion battery pack

### WARRANTY

- Limited lifetime warranty

### WHAT'S INCLUDED

- Lantern
- (1) Li-ion rechargeable battery (5500-BATT)
- Locking snap-in charger (5580-CHGR2)
- AC & DC power supply (NS-ACCORD & NS-DCCORD)
- Removable shoulder strap
- Instruction manual

| FL1 STANDARD | FLASH HIGH | FLASH LOW | DUAL-LIGHT |
|--------------|------------|-----------|------------|
|              | 210 LUMENS | 30 LUMENS | 300 LUMENS |
|              | 12h        | 65h       | 9h 15min   |
|              | 635m       |           |            |
|              | 101000cd   |           |            |
|              | 2m         |           |            |
|              | 1m         |           |            |

**Bayco Products, Inc. XPR-5580**  
**Wylie, TX 75098**

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS  
UL listed for use with Bayco Li-ion Battery Pack 5500-BATT

**UL LISTED**  
E 467756  
ID 4003544  
INTRINSICALLY SAFE  
SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T4  
CLASS II & III DIV 1 GRPS E-G  
CLASS I ZONE 0 GRP IIC T4  
CLASS II ZONE 20 IIC T135°C  
Ex ia IIC T4 Ga  
DEMKO 16 ATEX 1796  
UL220KEX2427  
IECEA UL 16.0154  
-20°C ≤ Tamb ≤ +40°C  
3.7V/Cell 5500-BATT  
U<sub>n</sub> = 4.75V

**CE** 2575 **UK CA** 0359

SEE INSTRUCTION MANUAL  
VOIR MANUEL

MFG MM-YY

