

Technical Data Sheet



Description

Description	93 A/St
Part Number	10115189
Marking according to EN	A2 - P3
Conditions of use	<ul style="list-style-type: none"> organic gases and vapors with a boiling point > 65° C particles



Colour code	<table border="1"> <tr> <td>brown</td> </tr> <tr> <td>white</td> </tr> </table>	brown	white
brown			
white			

Labels		
--------	--	--

Characteristics

Weight [g]	260
Diameter [mm]	107
Height incl. thread [mm]	78
Connection	EN 148 - 1

Breathing Resistance

	at	EN 14387 requirements	Typical values
	30 l / min	2,60 mbar	1,20 mbar
	95 l / min	9,80 mbar	4,60 mbar

Concentration of Testing Gases

Class 1	1000 ppm [0,1 Vol.-%]
Class 2	5000 ppm [0,5 Vol.-%]

Performances

Filter type and class	Gases of reference	EN 14387 requirements	Typical values
A2	cyclohexane [C ₆ H ₁₂]	35 min	60 min
Filter type and class	Particles of reference	EN 143 requirements	Typical values
P3	sodium chloride [NaCl]	0,05%	< 0,01%
	paraffin oil	0,05%	< 0,01%
R	Reusable according EN 143:2000/A1:2006		
D	Dolomite clogging test & marking according to EN 143:2000/A1:2006 and EN 14387		

Material

Housing	aluminium
Cover (particle filter)	polypropylene
Filtering material	filtering paper / impregnated activated carbon

Details/Special Information

Storage conditions & time	- 5 °C to + 50°C, < 90 % r. h. 6,0 years
---------------------------	--