

LI-ION RECHARGEABLE

XPR-5582RX
XPR-5582GX


INTEGRITAS™ INTRINSICALLY SAFE LANTERN

NIGHTSTICK®
Life Depends on Light™

1750

**POWERFUL
LUMENS**

INCLUDING HIGH & LOW



Rear green safety lights
provide visibility in smoke filled applications



Carry strap with seat belt style buckle for additional hands-free use



Convenient locking snap-in charger included



Dustproof/Waterproof (IP-67) and chemical/heat resistant for any environment



AVAILABLE IN MULTIPLE COLORS



FL1 STANDARD	HIGH	LOW
	1750 LUMENS	600 LUMENS
	5h	11h
	552m	325m
	81250cd	27083cd
	2m	1m

1750 LUMENS

INTRINSICALLY SAFE

PRODUCT SPECIFICATION SHEET

INTEGRITAS™

LANTERN

LI-ION RECHARGEABLE

ITEM NUMBER/UPC

XPR-5582RX (Red), UPC# 0 17398 806824
XPR-5582GX (Green), UPC# 0 17398 807029

MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- cETLus, CE, Meets requirements of NFPA-1971-8.6 (2013), Charger meets requirements of NFPA-1901 (2009) Mounted in any Position
- US Patent 9,713,217

CASE MATERIAL

- Glass filled nylon polymer

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 1750L, 5 hrs. runtime
- LOW: 600L, 11 hrs. runtime

CANDELA

FLASHLIGHT

- HIGH: 81,250
- LOW: 27,083

BEAM DISTANCE

FLASHLIGHT

- HIGH: 552m
- LOW: 325m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 7.54 in / 19.2 cm
- WIDTH: 4.26 in / 10.8 cm
- DEPTH: 5.83 in / 14.8 cm
- WEIGHT: 2 lbs. 11 oz. / 1219 g

BATTERY






- Rechargeable Li-ion battery pack

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Lantern
- Li-ion rechargeable battery pack
- Locking snap-in charger (5582-CHGR1)
- AC power supply
- DC direct wire kit with in-line fuse
- Removable shoulder strap
- Instruction manual

FL 1 STANDARD	HIGH	LOW
	1750 LUMENS	600 LUMENS
	5h	11h
	552m	325m
	81250cd	27083cd
		



Bayco Products, Inc. XPR-5582
640 S. Sanden Blvd., Wylie, TX 75098

ID 4003544
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CLASS I DIV 2 GRPS A-D T3
CLASS II & III DIV 2 GRPS F-G T135°C
CLASS I ZONE 2 Group IIC T3
-20°C ≤ Tamb ≤ +40°C
3.7V/Cell 5582-BATT



WARNING: Risk of ignition - Do not open in a hazardous area.
AVERTISSEMENT: Ne pas ouvrir dans une zone dangereuse.
WARNING: Risk of ignition - Do not charge batteries in a hazardous area.
AVERTISSEMENT: Danger d'incendie - Ne pas charger les piles dans une zone dangereuse.

CERTIFIED



NFPA



AVAILABLE IN MULTIPLE COLORS