

EVOLite®

MIDPEAK - WHEEL RATCHET - VENTILATED - CR2

TECHNICAL SPECIFICATION

PRODUCT CODE: AJB170-40 - _ 00

CR2 - HIGH INTENSITY REFLECTIVE OFFERING AN AVERAGE OF 60% MORE REFLECTIVITY THAN STANDARD REFLECTIVE CLOTHING MATERIAL

HEAD PROTECTION

INSTRUCTIONS FOR USE

Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head



SHELL:

High strength engineering grade ABS which has been UV Stabilised



CR2 REFLECTIVE:

High Intensity Reflective offering, on average, 60% more reflectivity than standard reflective clothing material



WEBBING HARNESS:

HDPE Strap & Webbing Clips with Polyester Webbing Straps

CHAMLON™ SWEATBAND:

Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested

SLIP RATCHET:

One Touch™ Slip Ratchet version of the EVOLite® is so simple to fit that it can be adjusted with just one finger



CR2 REFLECTIVE

EVOLite CR2 is the biggest step-up in night time visibility/reflectivity of head protection to date

Meeting reflective performance requirements of EN12899-1 (High performance reflective sign face material)

CONFORMITY

EN 397 for Industrial Safety Helmets

EC Certificate Number 00279, issued by BSi Product Certification

Meets optional Lateral Deformation performance

Meets optional Molten Metal Splash performance

Wide size range. Slip or wheel ratchet - High comfort fit

Available vented. Available with mid or micro peak

Company personalisation available by printing

EvoLite®

MIDPEAK - WHEEL RATCHET - VENTILATED - CR2

TECHNICAL SPECIFICATION

PRODUCT CODE: AJB170-40 - _ 00

CR2 - HIGH INTENSITY REFLECTIVE OFFERING AN AVERAGE OF 60% MORE REFLECTIVITY THAN STANDARD REFLECTIVE CLOTHING MATERIAL

HEAD PROTECTION

DIMENSIONS OF OUTER PACKAGING

Quantity: 10

Weight: 3.2kg (Approx.)



HEIGHT:
450mm

WIDTH:
240mm

LENGTH:
580mm



HELMET FEATURES

| | | |
|------------------------|--|--------------------------------|
| EN STANDARD | EN397 EN12899-1 | Yes Yes |
| PERFORMANCE | Impact Resistance Lateral Deformation | Yes 50 Joules Yes |
| TEMPERATURE RESISTANCE | Molten Metal (MM) +50°C -30°C | Yes Yes Yes |
| SHELL MATERIAL | ABS Recyclable UV Stabilised | Yes Yes Yes |
| HARNESS MATERIAL | HDPE Textile | Yes Yes |
| OPTIONS | Universal Accessories Reflective CR2 option Integrated Eyewear | Yes Yes Yes |
| HARNESS SYSTEM OPTIONS | JSP 3D Slip Ratchet 6 pts | Yes Yes Yes |
| CHINSTRAP OPTIONS | 4 pts 2 pts | Yes Yes |
| LOGO OPTIONS | Front Rear Side MOQ Logo Individual Name | Yes Yes Yes 10 Yes |

DIMENSIONS OF HELMET

Size: 530 - 640mm

Weight: 299g (Approx.)

CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature



HELMET COLOURS

Insert the following two digit number in place of the dashes in the product code of your desired helmet



01 White

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer