

The ideal solution to mitigate static buildup when working with chemicals and liquids in environments with static hazards or high explosive risks



- Nitrile barrier provides advanced chemical protection from many frequently used chemicals.
- AlphaTec 58-001 has Type A chemical protection under new ENISO 374:2016
- Unique Nitrile composition which allows effective dissipation of static build up. Vertical resistance $<1 \times 10^8$
- For complete chemical permeation information, please visit: www.ansellguardianpartner.com
- Compliant to EN16350 Volume resistance

Industries

- Agriculture
- Automotive
- Food Processing
- Life Sciences
- Machinery and Equipment
- Metal fabrication
- Oil and gas
- Recycling and Waste Disposal
- Chemical

Applications

- Assembly & inspection of components
- Oil, fluids and filter change
- Plating, coating, sealing, painting
- Handling incoming goods
- Transferring liquids and solids between vessels and tanks and process equipment
- Opening furnaces draining pumps valves or lines and crackers BTX process
- Cleaning furnaces, distillation pumps, valves or lines and crackers BTX process

Key Features

- High performance Nitrile compound offers a far superior snag, puncture and abrasion protection compared with rubber or Neoprene gloves
- Reverse lozenge palm finish for improved dry/wet grip
- Foldable cuff gutter to prevent dripping on the forearm
- Antistatic flocking layer for ease of donning/doffing and moisture management



Performance Standards

EN388: 2016



4101X

EN ISO 374-1:2016



AJKLOPT

EN ISO 374-5



VIRUS

EN 1149



EN 16350



EN 16350



Specifications

BRAND STYLE	DESCRIPTION	SIZE	LENGTH	COLOR	PACKAGE
AlphaTec® 58-001 ESD	N/A, Nitrile,	7, 8, 9, 10, 11	330 mm / 12.9 inches	Green	• 12 pairs per bag, 12 bags in a carton