



**PRODUCT INFORMATION**

<b>Item Number</b>	RE4410
<b>Size Range</b>	8-11
<b>Primary Coating Polymer</b>	Latex
<b>Max Working AC Voltage</b>	36000.00 V

**FEATURES**

**Electrical Handling:** Class 4, for a maximum working AC voltage of 36000V

**Length:** 41cm length for extended protection up the arm

**Flexibility:** Industry leading latex manufacturing techniques and expertise allows gloves to be as soft and thin as possible offering the maximum level of the dexterity to the user

**Chemical Resistant:** Passes special properties 'AZC' for protection against acid, ozone and extremely low temps

**Electrical Handling:** Designed to be used in conjunction with our leather Protector Gauntlet (RE-PRO & RE-PRO/NB) for additional longevity and mechanical protection  
Excellent electrical resistance

**Lining:** Lightly powdered to ensure easy donning and doffing

**SECTORS**

Automotive • Construction & Utility

**STANDARDS**



PPE CAT III



0333



**CAUTION**

**Contains latex which may cause allergic reactions, including anaphylactic response.  
Contains accelerator chemicals which may cause type IV skin irritation and contact dermatitis in sensitised individuals.**

**STORAGE INSTRUCTIONS**

Store in dry conditions, away from direct sunlight and extreme heat. You are advised to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear.

**DISPOSAL INSTRUCTIONS**

Dispose of responsibly and in line with local guidance.

**PACKING**

1 pair per bag  
280 pairs per pallet

Size	Outer Packaging Barcode
9	05010699855640
10	05010699855657
11	05010699855664