

BL30

B-LINE is a range of safety eyewear **accessible to all** and is adapted to the most common industrial risks. **B-LINE** benefits from Bollé Safety's expertise and quality.

The BL30 offers an excellent quality/price ratio. It has an ultra **wrap-around fit** that perfectly meets all types of needs for your company. Equipped with an **anti-scratch and anti-fog coating** on both sides of the lenses, BL30 ensures absolute long-lasting comfort.

B LINE



PSSBL30-014



PSSBL30-408



PSSBL30-047*



PSSBL30-016*



PSSBL30-013*



PSSBL30-010*



PSSBL30-048*



24 g

***5 CHOICES OF TEMPLES COLOURS**

On demand from 4800 pieces // Non-stocked items

- + UPPER PROTECTION**
- + ANTI-FOG & ANTI-SCRATCH COATING ON BOTH SIDES OF THE LENSES**
- + LIGHTWEIGHT**
- + STOP-IN SYSTEM (ON THE HINGE OF THE TEMPLES)**
- + UNIVERSAL FIT**
- + WITHOUT ANY SCREWS**

bollé
SAFETY

BL30

MODEL	VERSIONS	TEMPLER COLOURS	REFERENCES	LENS MARKINGS			FRAME MARKINGS			COATINGS	
				EN166	ANSI	AS.NZS	EN166	ANSI	AS.NZS		
BL30	IN STOCK	Smoke	Smoke	PSSBL30-408	5-2,5 ☞ 1FT ☞	☞Z87+U6L2.5	☞ I2	☞EN166 FT☞	☞Z87+	AS/NZS 1337.1:2010	ASAF
		Clear	Clear	PSSBL30-014							
	ON DEMAND	Clear	Orange	PSSBL30-047	2C-1.2☞1FT ☞	☞ Z87+U6	☞ I0	☞EN166 FT ☞	☞ Z87+	AS/NZS 1337.1:2010	ASAF
		Clear	Yellow	PSSBL30-016							
		Clear	Grey	PSSBL30-013							
		Clear	Blue	PSSBL30-010							
		Clear	White	PSSBL30-048							

LENS MARKINGS

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- I.** The letter «I» signifies «Medium Impact» approval.
- O.** The letter «O» signifies that the product has been approved for the use both outdoors and indoors.

Others symbols:

- ☞ European standard ☞ Manufacturer name
- O.** Range of luminous transmittance 80-100% (clear)
- 2.** Range of luminous transmittance 18-43% (smoke)

FRAME MARKINGS

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

Z87+ : Impact rated for Plano product - tested and approved to ANSI Z81.1-2015

AS/NZS 1337.1:2010 : Tested & approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

☞ European standard ☞ Manufacturer name

Bollé Safety product approval certificates to standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

