


Cushion Link Solid Top - Abrasive

Cushion Link Solid Top is a modular anti-fatigue matting system. The abrasive finish provides exceptional anti-slip protection as well as providing outstanding ergonomic comfort and safety in heavy duty or dry industrial areas. Manufactured from the highest quality resilient rubber compounds, Cushion Link Solid Top - Abrasive contains 100% nitrile making the product resistant to extreme temperatures, oils, coolants and most chemicals. The adaptable solid top design is also compatible with our Cushion Link Open Top range.

All Cushion Link mats can be interlocked and edged using a simple bevel system to create any size or shape, whilst the unique interlocking mechanism along with male and female edges and bevels, provide secure connectivity. This product is also compatible with our Cushion Link Open Top range.

Features

- ◆ **Typical applications:** Perfect for oily, greasy, welding and manufacturing areas.
- ◆ **Material:** Natural rubber, recycled rubber and nitrile rubber.
- ◆ **Cleaning:** Wash with cold water, use vacuum cleaner, or use a pressure pump to remove dirt.
- ◆ **Sustainability:** Nature friendly, biodegradable and recyclable. REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- ◆ **Warranty:** Lifetime.



Black only. Bevels available in both black and yellow



For our icon glossary please visit: bluediamond.uk.com/glossary
For more information about this product or, to place an order [click here](#)

Code	Metric	Imperial	Thickness	Weight	Type	Colour
CLS36NFRA	92cm x 92cm	3' x 3'	19mm	10.2kg	Mat	Black
CLS36BBF	92cm long	3' long	19mm	0.75kg	Bevel - Female	Black
CLS36BBM	92cm long	3' long	19mm	0.90kg	Bevel - Male	Black
CLS36YBF	92cm long	3' long	19mm	0.75kg	Bevel - Female	Yellow
CLS36YBM	92cm long	3' long	19mm	0.90kg	Bevel - Male	Yellow

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

Cushion Link Solid Top - Abrasive

Technical Specification

Slip resistant:	Excellent slip resistant to level 3, this product is recommended for extremely slippery areas (slip resistant R13 according to DIN51130)
Anti-fatigue:	Excellent anti-fatigue properties, resistant to level 3
Wear resistant:	Excellent wear resistance to level 3, suitable for heavy footfall
Chemical resistant:	Yes
Connectable:	Yes, the mats are modular and interlocking with bevelled edges to create ramps to all sides
Cut to size:	Yes, mat can be cut to bespoke sizes
Disability friendly:	Yes, the mats have ramped edges making them suitable for wheelchair users
Dry area:	Yes
Oily and greasy area:	Yes
Heavy area:	Yes
Welding area:	Yes
Wheeled area:	Yes
Environment:	Suitable for indoor and outdoor use
Flame retardant:	Yes
Impact resistant:	Yes
Product testing:	<ul style="list-style-type: none"> ◆ Tensile strength: 3-3.5 Mpa ◆ Hardness: 55+ Shore A ◆ DIN abrasion loss mm³: 250-300 ◆ Elongation at break: 200-250%
Sustainability:	<ul style="list-style-type: none"> ◆ Nature friendly, biodegradable and recyclable ◆ REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals) ◆ Contributes to a cleaner environment by reducing the need to use cleaning chemicals
Temperature resistance:	-20°C to +30°C
Cleaning:	Wash with cold water, use vacuum cleaner, or use a pressure pump to remove dirt. The use of hard detergents is not recommended