

Chemsplash Standard Overshoe Type 5B & 6B PB

Code: 2560

Description:

Chemsplash 55GSM Type 5B&6B PB
Material
16" In Length
Non-Linting
Anti-Static Material

Sizes: L - 2XL

Colours Available: White

Pack Quantity:

Number of Units In Inner Case 10
Number of Units In Outer Case 200

FABRIC PHYSICAL PROPERTIES	TEST METHOD	RESULT	EN CLASS*
Abrasion resistance	EN530 (method 2)	>10 Cycles	1
Flex cracking resistance	ISO7854 (method B)	>5000 <15000 cycles	3
Trapezoidal tear resistance	ISO9073-4	MD=58.31N CD=30.72N	2
Tensile strength	ISO13934-1	MD=121.6N CD=54.9N	1
Puncture resistance	EN863	10N	1
Repellancy to liquids	EN368		
	30% Sulphuric Acid	96.70%	3
	10% Sodium Hydroxide	97.90%	3
	o-Xylene	91.40%	2
Resistance to penetration by liquids	Butan-1-ol	95.60%	3
	EN368		
	30% Sulphuric Acid	0.00%	3
	10% Sodium Hydroxide	0.00%	3
	o-Xylene	0.00%	3
	Butan-1-ol	0.00%	3
Surface resistivity **	EN1149-1:2006 EN1149-5:2008	<2.5 x 10 ⁹ Ohm	N/A

Protection Limit:

The protection against risks or hazards which are not mentioned on this document are not warranted. The levels of performance mentioned are only valid for new products, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

Storage:

Keep this product in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated environment.



Applicable Standards:
EN13982-1 TYPE 5B PB
EN13034 TYPE 6B PB
EN1073-2 NUCLEAR PARTICLE
EN1149-5 ANTI-STATIC
CAT1 Partial Body Protection