

VENICUT50



HEATNOCUT KNITTED GLOVE - COWHIDE LEATHER PALM Ref. VECUT50





Product specifications

HEATnocut high performance polyethylene fibre. Cowhide leather on palm and fingertips. Gauge 10.

Support: HEATnocut fibre (high performance synthetic fibres). Split cowhide.

COLOUR

Yellow-Grey

SIZE

09, 10

Product Use - Risks



. . .



CUTTING



Wearing



Construction / Civil engineering



Heavy industry



Light industry



Services / Logistics



Oil / Gas



Mining



Product's highlights & user's benefits HEATnocut High Performance Polyethylene Split leather Contact heat (250°C for 15 seconds) and cut resistance Very good level of abrasion resistance Suitable for heavy work Cut level D Cut level D



Certifications and Standards

$C \in$

REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

1: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

- 4: Resistance to abrasion (from 1 to 4)
- X: Resistance to cutting (from 1 to 5)
- 4: Resistance to tear (from 1 to 4)
- 3: Resistance to puncture (1 to 4)
- D: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)



- 1: Contact heat resistance (from 1 to 4)
- X: Convective heat resistance (1 to 4)
- X: Radiant heat resistance (from 1 to 4)
- X: Small splashes of molten metal (from 1 to 4)
- X: Large quantities of molten metal (from 1 to 4)

USA STANDARDS

ANSI

ANSI-ISEA 105:2016 Hand protection

A4: Resistance to cutting by sharp objects (from A1 to A9)

References					
References	Bar code	COLOUR	SIZE	•	À
VECUT5009	00	Yellow-Grey	09	60	12
VECUT5010	3295249157296	Yellow-Grey	10	60	12