

## VENICUT 52



HEATNOCUT® KNITTED GLOVE - LATEX-COATED PALM

Ref. VECUT52



### Product specifications

HEATnocut® high performance polyethylene fibre. Latex coating on palm and fingertips. Gauge 10.

Support: HEATnocut® fibre (high performance synthetic fibres).

Coating : 100% latex.

#### COLOUR

Yellow-Black

#### SIZE

07, 08, 09, 10

### Product Use - Risks



Heat



CUTTING



Wearing



Construction / Civil engineering



Heavy industry



Light industry



Services / Logistics



Wind energy

Product's highlights & user's benefits



Latex coating

Good resistance to abrasion  
Rough finish for excellent grip on handled objects

HEATnocut® High Performance Polyethylene

Contact heat (250°C for 15 seconds) and cut resistance  
Very good level of abrasion resistance



Cut level D

## Certifications and Standards



### REGULATION (EU) 2016/425

**EN420:2003+A1:2009 General requirements**  
3: Dexterity (from 1 to 5)

**EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)**  
3: Resistance to abrasion (from 1 to 4)  
X: Resistance to cutting (from 1 to 5)  
4: Resistance to tear (from 1 to 4)  
2: Resistance to puncture (1 to 4)  
D: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



**EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)**  
X: Resistance to flammability (from 1 to 4)  
2: Contact heat resistance (from 1 to 4)  
X: Convective heat resistance (1 to 4)  
X: Radiant heat resistance (from 1 to 4)  
X: Small splashes of molten metal (from 1 to 4)  
X: Large quantities of molten metal (from 1 to 4)





### USA STANDARDS

**ANSI-ISEA 105:2016 Hand protection**  
A3: Resistance to cutting by sharp objects (from A1 to A9)



## References

References	Bar code	COLOUR	SIZE		
VECUT5207	3295249150778	Yellow-Black	07	60	12
VECUT5208	3295249158484	Yellow-Black	08	60	12
VECUT5209	3295249150785	Yellow-Black	09	60	12
VECUT5210	3295249150792	Yellow-Black	10	60	12