



WATERPROOF FLAME RETARDANT GLOVES

- EN407 Burning Behaviour Level 4
- EN388 Cut Resistance Level 3
- Close fitting, waterproof, windproof and breathable
- Protection from Weak Chemicals and Micro-organisms
- Tough outer layer made from Kevlar®
- Excellent grip and dexterity
- Patented, seamless 3 layer construction



GLOVES



DESCRIPTION

Fully waterproof, windproof and breathable glove with great dexterity. A knitted Kevlar® outer gives a high level of mechanical protection and flame retardancy. The Merino wool inner also provides excellent burning behaviour, warmth and wicking performance. Grip dots on the palm enable excellent grip in the wet. Incorporates SealSkinz® patented, seamless 3 layer construction consisting of a knitted outer glove, a protective membrane barrier and a knitted inner glove.

USAGE

Ideal for high protection against abrasion, cut, tear and puncture where a high level of flame retardancy is also required. Provides resistance to Micro-organisms, Weak Chemicals, Sand, Gravel and Grit.

PRODUCT CODE AND COLOURS

DG831 Grey

GLOVE SIZES AVAILABLE

S M L XL

THERMAL RATING



Our thermal rating system grades the products from ONE to FIVE to indicate the relative warmth of our products. Products with a thermal rating of ONE are lighter weight and/or thinner. Products with a thermal rating of FIVE are heavier weight and/or thicker.



All SealSkinz® DUTY products are manufactured in the United Kingdom at our own factory in King's Lynn in accordance with our ISO 9001 registered quality control system.

SealSkinz® Limited
36 Oldmedow Road, Hardwick Industrial Estate, King's Lynn, Norfolk, PE30 4PP
Tel: +44 (0)1553 817990 Fax: +44 (0)1553 772662 Email: info@sealskinz.com www.sealskinz.com

PERFORMANCE AND LIMITATIONS OF USE

These products have been tested in accordance with:

EN 407:2004



4 2 3 3

EN 407:2004 Property	Performance Level Achieved	(Maximum Performance Level)
Burning Behaviour	4	(4)
Contact Heat	2	(4)
Convective Heat	3	(4)
Radiant Heat	3	(4)

EN 388:2003



3 3 4 2

EN 388:2003 Property	Performance Level Achieved	(Maximum Performance Level)
Abrasion Resistance	3	(4)
Blade Cut Resistance	3	(5)
Tear Resistance	4	(4)
Puncture Resistance	2	(4)

EN 374-2:2003



EN 374-2:2003



Protection against Micro-biological Hazards, Micro-organisms, Weak Chemicals, Sand, Gravel, Grit, fully waterproof with breathability in excess of 65% W.V.P.

MARKING

The product is marked with:

- The CE mark
- The manufacturer
- The product code
- The size

Certification Body

SATRA Technology Centre,
Kettering, Northants,
NN16 8SD, UK
(Notified Body: 0321)

WASHING INSTRUCTIONS

The gloves may be machine washed at 40°C and have achieved the maximum wash cycles during testing without loss of standards or degradation.



Wash at 40°C



Tumble dry low



Do not dry clean



Do not iron



Do not bleach

MATERIALS

Inner 84% Merino wool, 16% Elastane
Outer 85% Kevlar®, 15% Elastane
Membrane FR PU



ISO 9001