

Description:

The Elite Delta Light Mains is the original Delta Light evolved from the industry leading Elite Aurora Light. The versatile base ensures stability and includes 2 power outlet sockets and integral cable management system for increased functionality and user convenience. The high output 360° light distribution delivers 3600lm of crisp white light from energy efficient LEDs.

Part No. **DL36**

Specification:

- 36W 3600lm output
- 1200mm diffusor height – illuminates a standard ceiling without shadowing
- Carry handle in centre of product, perfectly balanced, and weighted base for stability
- Solid state LED technology
- CRI >80 and colour temperature of 6400K
- Fully CE / UKCA compliant and manufactured to meet IP54 and IK08.

Differentiator:

- Small footprint base, no wide tripod to trip over!
- Full 360 light distribution.
- 1 Product – 1 fleet number – easier fleet management!
- All components are manufactured from robust materials to ensure the product performs in the harshest environments

Technical:

- Voltage – 110V 50/60Hz
- Plug – 110V 16A IEC60309
- Sockets – 2X 110V 16A IEC60309
- Weight – 4.1kg
- Dims – 380 x 330 x 1200mm (LxDxH)
- Power setting – 1 (100% 3600lm)



LUMENS
3600Lm



VOLTAGE
110V



ROUGH SERVICE



-10° TO +40° CELSIUS



CABLE MANAGEMENT



360°
LIGHT SPREAD



IP54



For more
quality
products
please
scan here

