



Ultimate Industrial

HAND PROTECTION RANGE



TECHNICAL PRODUCT DATASHEET

COLD PROTECTION



HEAT PROTECTION



UPDATED: 23/12/2020

TCG32D6

32oz heat resistant terry gauntlet with extended canvas cuff.

A traditional cut and sewn style terrycloth range offering heat protection up to 250°C. Heavyweight 32oz cotton terrycloth is soft and comfortable for the wearer and also offers cut protection to level 2. This gauntlet has a duck canvas cuff to increase protection to the lower arm.



FEATURES AND TECHNOLOGY



HEAT TESTED



COLD CONDITIONS



EXTRA LONG

TYPICAL INDUSTRIES



GENERAL PURPOSE



MANUFACTURING



STEEL & METAL



CATERING



GLASS

TECHNICAL INFORMATION

| | |
|--------------------------|--|
| ORDER REF # | G/TCPT32D16 |
| COATING MATERIAL | N/A |
| PACKING | PER PACK: 6 x Pair PER CASE: 60 x Pair |
| SIZES AVAILABLE | 10/L-XL |
| EU TYPE CERTIFICATION BY | SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, Dublin, D15 YN2P, Ireland (Notified Body No. 2777) |

CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)

EN388:2016

2 2 3 2 X

Abrasion (0-4)
Cut (0-5)
Tear (0-4)
Puncture (0-4)
TDM Cut (A-F)

EN388:2003*

2 2 3 2

Abrasion (0-4)
Cut (0-5)
Tear (0-4)
Puncture (0-4)

EN407:2004

X 2 X X X X

Contact Heat

¹ 'X' denotes not tested.
² * Where applicable, EN388:2016 scores take precedent and are ongoing.
³ There is no correlation between coupe test levels and EN ISO 13997 / TDM cut test levels.

CAT II



Ultimate Industrial

HAND PROTECTION RANGE



TECHNICAL PRODUCT DATASHEET

COLD PROTECTION



HEAT PROTECTION




UPDATED: 23/12/2020

CERTIFICATION LEGENDS

EN388:2016



EN388:2016
Blade Cut TDM
EN ISO 13997 *



* For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

NEWTON LEVEL

| | |
|------|---|
| ≥ 30 | F |
| ≥ 22 | E |
| ≥ 15 | D |
| ≥ 10 | C |
| ≥ 5 | B |
| > 2 | A |

EN407:2004



EN511:2006



* For details regarding maximum permissible user exposure, see separate sheet.

¹ Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. ² 'X' denotes Not Tested. ³ Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between coupe test levels and ISO 13997 / TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational purposes only.

FURTHER INFORMATION

STORAGE / TRANSPORT: Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

PRECAUTIONS BEFORE USE: 1. Never use these gloves with chemicals. 2. Gloves should not be used when there is a risk of entanglement with moving machine parts. 3. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 4. The gloves should not come in contact with a naked flame or fire. 5. Do not subject to high speed or serrated blades. 6. Always read enclosed user instructions before using these gloves. 8. The information provided is for products in a new condition and does not reflect the actual duration of protection in the workplace. 9. Service life cannot be specified and depends on the application and the responsibility of the user to ascertain suitability of the glove for its intended use.

CONSTITUENTS / ALLERGIES: Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.