



Data Sheet | Model:

Armorgard FlamBank FB21

- Strong hazardous vault for storing hazardous goods safely and securely.
- Keyed alike 5-lever deadlocks.
- Unique external and internal anti-jemmy system.
- Robust construction using 2mm and 3mm steel.
- Hydraulic gas arms to assist with the lid opening.
- Autolatch lid stay to secure the lid in the open position.
- High and low level ventilation to prevent build-up of fumes.
- Flame arrester gauze fitted.
- The FlamBank is built to the specification of 30 minute fire resistance.
- Suitable for storing flammable equipment or chemicals.
- Fully welded sump to comply with COSHH regulations and prevent any leakages.
- Fork lift skids with fixing holes to add castors and make it a mobile unit.
- Facilities to fix the unit in position.
- Complete with relevant signage.

Product	Armorgard FlamBank FB21
Internal dimensions	675x605x575mm
External dimensions (including protrusions)	765x675x670mm
Weight	64kg
Colour	Pillar Box Red: RAL 3020
Finished coating	Powder coated steel
Material	Steel
Material thickness	2mm and 3mm
Locking mechanism	2x highly secure, keyed alike 5-lever deadlocks
Does it have forklift skids?	Yes
Does it have gas arms?	Yes
Newton loading of gas arms	300N
Safety stay	Yes
Quantity of keys supplied	3 keys
Optional extras available	Castors
Quantity of shelves as standard	0
Are castors standard or optional extra	Optional Extra
How are the castors fitted?	Quick-fix bolt on castor kit
Sump capacity	40L
Safety signage	Hazardous goods sign
Fire resistant?	Yes

