



Data Sheet | Model:

Armorgard TransBank TRB3

- Fully welded, bunded unit, for storing and transporting fuels and chemicals.
- Rear ventilation allows airflow and helps prevent the build up of fumes.
- External fixing points to secure the unit to the floor.
- Over-centre clasp with hasp and staple padlock facility.
- Fitted with flame arrester gauze and built to the specification of 30 minute fire resistance.
- Suitable for storing fuels or chemicals.
- Pitted with hazardous warning signs.
- Designed for storing 3 x 20 litre cans.

Product	Armorgard TransBank TRB3
Internal dimensions	620x415x510mm
External dimensions (including protrusions)	705x485x540mm
Weight	24kg
Colour	Pillar Box Red: RAL 3020
Finished coating	Powder coated steel
Material	Steel
Material thickness	1.2mm
Locking mechanism	Hasp and staple with padlock facility
Does it have forklift skids?	No
Does it have gas arms?	No
Newton loading of gas arms	N/A
Safety stay	No
Quantity of keys supplied	N/A
Optional extras available	50mm Padlock (PAD-50)
Quantity of shelves as standard	N/A
Are castors standard or optional extra	N/A
How are the castors fitted?	N/A
Sump capacity	70L
Safety signage	Hazardous goods sign
Fire resistant?	Up to 30 minutes

