

3M™ Protecta® Shock Absorbing Lanyard, Rope, Single Leg, 1.38 - 2.00 m

Product Type: Lanyard

Part Number: 1260353

Description

Sub-brand:	Protecta®
Industry:	Various
Applications:	Various

Features

Lanyard:	<ul style="list-style-type: none"> Type: Fall Arrest Leg Type: Single Rope Leg Material: Polyamid / Polyester
Connector-A:	<ul style="list-style-type: none"> Type: Oval Carabiner <ul style="list-style-type: none"> Locking: Screw-Gate Breaking Strength: 25 kN Opening: 17 mm Material: Steel - Zinc Plated
Connector-B:	<ul style="list-style-type: none"> Type: Oval Carabiner <ul style="list-style-type: none"> Locking: Screw-Gate Breaking Strength: 25 kN Opening: 17 mm Material: Steel - Zinc Plated
Length:	Adjustable: 1.38 - 2 m
Weight Capacity:	<ul style="list-style-type: none"> Min: 50 kg Max: 130 kg Maximum Peak Force*: <6 kN
Net Weight:	0.8 kg
Operating Temperature:	-35°C +57°C
Standards:	CE EN355:2002

*Tested using standard EN 355 across weight capacity.



Important notice

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable national and/or European regulations and standards. Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: A limitation of liability applies to the 3M product(s). For warranty statement and limitation of liability, refer to your supply agreement or the 3M terms & conditions of sale.

3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use.

