



Oil

Low Chemical Protection



Light Duty

Ultralight abrasion-resistant gloves with special oil-repellent capabilities

- **Enhanced grip:** Three quarter-dipped coating featuring Improved ANSELL GRIP™ Technology provide 20% higher grip* in wet and oily conditions minimizing required force for safer handling
- **Specialized protection:** Improved HyFlex® 11-925 industrial gloves' RIPEL™ Liquid Repellence surface barrier averts skin contact with oil or chemicals for increased oil protection and permeability
- **Increased flexibility:** HyFlex® 11-925 safety gloves' ergonomic hand shape and ultralight fine-gauge liner help reduce hand fatigue and augment dexterity
- **Elevated comfort:** The blend of Spandex® and Nylon® in these HyFlex® gloves' liner also grants them a “second skin” sensation of lightness and comfort
- **Touchscreen compatible:** These industrial gloves work with multiple touchscreen devices - no need to remove them when switching between tasks for workplace safety
- **Enhanced defenses:** HyFlex® 11-925 industrial gloves feature EN407 heat contact level 1 resistance allowing occasional handling of hot objects at temperatures up to 100°C/212°F (for 15 seconds)



Industries

- Automotive
- Machinery and Equipment
- Chemical
- Agriculture
- Oil and gas

Applications

- Assembly & inspection of components
- Assembly and disassembly of equipment
- Assembling and mounting components
- Inspection (picking, checking and marking)
- Mounting and dismantling
- Handling outgoing goods: cans, vessels, bulkpack and cartons
- Loading trucks & vehicles
- Product shipping, transport and delivery

HyFlex®

ADVANCED MECHANICAL PROTECTION

11-925

Ultra-light duty oil repellent, oil grip multi-purpose glove

Key Features

- **Improved ANSELL GRIP™ coating:** up to 20% higher grip in wet and oily conditions*
- **Three-quarter dipping:** For defensive coating with ample grip
- **Ultralight fine-gauge liner:** Highly flexible, dexterous hand protection

*vs previous technology version

Vulcanization Chemical Accelerators

- Zinc Dibutyldithiocarbamate

Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.

Performance Standards & Regulatory Compliance



Technologies



Specifications

| BRAND STYLE | DESCRIPTION | Gauge | SIZE | LENGTH | COATING COLOR | PACKAGE |
|----------------|---|-------|--------------------|------------------------------|---------------|--|
| HyFlex® 11-925 | Finishing: ¾ Coated Coating Material: Nitrile Liner Material: Nylon, Spandex Cuff Style: Knitwrist | 18 | 6, 7, 8, 9, 10, 11 | 205-250 mm/ 8.07-9.84 inches | Black | <ul style="list-style-type: none"> • 12 pairs in a bag; 12 bags in a carton |