

**Product Datasheet
model 9906 003 uvex pheos visor magnetic**



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

Product characteristics

- PC visor with uvex supravision excellence coating technology
- Magnetic locking system
- Visor can be removed from the helmet at any time via magnetic click system
- Visor can be placed over the helmet shell into a parking position
- Well-balanced system, ergonomic relief for the wearer
- Marking 3 (drops and splashes of liquid) and 9 (molten metal and hot solids)
- Can be combined with uvex pheos industrial safety helmet B-S-WR and uvex pheos alpine safety helmet for working at height (a visor adapter 9790.067 is required for combination with the uvex pheos alpine helmet)
- Compatible with earmuffs uvex pheos K2P magnetic (2600.215)

Technical details	
Frame	
Material	PE
Colour	Black
Marking of support body	
Manufacturer's ID code	W
EN Norm	166
Area of application	3 (drops and splashes of liquid) 8-2 (arc fault according to GS-ET 29) 9 (molten metal and hot solids)
Mech. strength	B (120 m/s)
Conformity symbol	CE
No. of notified body	0196
Vi Lens	
Material	PC
Thickness	2,2 mm
Coating	uvex supravision excellence
Colour	Colourless
UV protection	UV 400
Marking of the visor plate	
Filter	2C-1,2 (EN 170)
Manufacturer's ID code	W
Optical class	1
Mech. strength	B (120 m/s)
Area of application	9 (molten metal and hot solids)
Surface resistance to fine particles	K
Anti-Fog	N
Conformity symbol	CE
Miscellaneous	
Weight	176 g
Packaging	Individually packed in polybag 20 pcs in a carton
Standards	EN 166 + EN 170
PPE Category	Category II

Spare parts and accesories:

Art.-Nr. 9906013	Replacement visor
Art.-Nr. 9790067	Visor adapter combination with uvex pheos alpine helmet
Art.-Nr. 9790074	Sun/rain protection screen for visor
Art.-Nr. 9954362	Storage bag for visors