






Olympic-S2



REF.	FA 20 502 02
LG. 	2.0 m
KG	MAX. 140 KG
CE	EN 360:2002
MAT. 	Polyamide 6 - 30% fiber glass Aramid 21 mm
	STEEL / ALU FA 50 101 17 / FA 50 221 17 with fall indicator
	x2
R(kN)	15 kN
	YES – 100 KG
+	FACTOR 2 – 100 KG
	0.77 KG



Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers

MAT.



Matière carter / sangle
 Material of casing / webbing
Material cárter / correa
 Material dei carter / Cinghia
Material Gehäuse / Gurt



Matière connecteur haut / connecteur bas
 Material of top connector / bottom connector
Material conector alto / conector bajo
 Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement



Nombre d'émerillons
 Number of swivels
Cantidad de eslabones giratorios
 Numero di tornichetti
Anzahl der Wirbel



Homologué pour le travail à proximité d'arêtes vives
 Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
 Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten