

Bitumen Cold Joint Sealer

Durable, Instant Sealing Solution

Lapwing

Product Code: **25BCS750**

Delivering a Durable Seal on Vertical Edges Quickly

Bitu-Spray protects repairs against water ingress and improves durability by protecting surface reinstatement in all weather conditions.

Features:

- **Fast Drying** - Touch dry in just 5 minutes
- **Easy Application** - Spray action for quick, simple use
- **Great Coverage** - Bitumen formulation ensures thorough seal
- **Weather Resistant** - Can be used in all conditions
- **Durability** - Improves repair longevity and prevents freeze-thaw damage
- **Economical** - No waste, eliminates brush application
- **Convenient Size** - 750ml can be suitable for various tasks

Applications:

Shake can vigorously before use, invert and spray 20-25cm from surface for even coverage. Point can upright and spray a few seconds to clear nozzle after use.

Suitable for sealing vertical edges of trenches, road, and ironwork reinstatements. Also repairing felt roofs, guttering, and general damp proofing.

Specifications:

Appearance: Black thixotropic liquid

pH: Not applicable

Specific Gravity: 0.91-0.94

Non-Volatiles / Active Content: 35-45% m/m

Flammability: Extremely flammable, flash point <20°C

Composition: Blend of bitumastics and thixotropes in hydrocarbon carrier solvents; propelled by mixed butane, propane, and dimethyl ether

