

## Safety Helmet User Sheet

H8101 (White)  
H8102 (Blue)  
H8103 (Red)  
H8104 (Yellow)  
H8105 (Pink)  
H8106 (Black)

Safety helmet has been designed in accordance with EN 397:2012 + A1:2012 as well as the health and safety requirements of the PPE Regulation (EU) 2016/425

Notified Body: 2777. Satra Technology Europe Ltd, Bracetown Business Park, Clonee, Dublin, D15 YN2P, Ireland

### PROTECTION CLASS AND LIMITS OF USE

For adequate protection this helmet must fit or be adjusted to the size of the user's head. The helmet is made to absorb the energy of a blow by partial destruction or damage to the shell and the harness, and even though such damage may not be readily apparent, any helmet subjected to severe impact should be replaced.

The attention of users is also drawn to the danger of modifying or removing any of the original component parts of the helmet, other than as recommended by the helmet manufacturer. Helmets should not be adapted for the purpose of fitting attachments in any way not recommended by the helmet manufacturer.

Do not apply paint, solvents, adhesives or self-adhesive labels, except in accordance with instructions from the helmet manufacturer.

### THE SAFETY HELMET MUST BE USED:

For protection against impacts from objects such as stones, bricks and other objects of similar weight, as well as for general masonry and construction work.

### INSTRUCTIONS FOR PROPER USE OF THE SAFETY HELMET

Position the safety helmet on the head so that the harness fits around the skull and the sweat band is on the forehead. To use effectively, adjust the neck strap so the safety helmet fits snugly. The height may be adjusted to one of three different position for use. The safety helmet may not be modified under any circumstances for attaching accessories that are not recommended by the manufacturer.

### INSPECTION

Before being used, the equipment must be inspected to check that the harness anchors are well attached and the buffering straps are in good condition.

### STORAGE AND TRANSPORT

When not in use place the safety helmet in its original packaging or in a bag for storage or transport. The safety helmet must be stored in a dry place, away from heat sources and away from direct sunlight.

### CLEANING

Wipe clean with a damp cloth

### SERVICE LIFE

The theoretical service life of the equipment is 5 years from the moment it is put into use, as long as it has been stored in compliance with storage conditions.

The actual service life of the equipment will depend on the intensity and frequency of use, the work environment, the skill of user, maintenance, storage, etc.

It is preferable for users to have their own specific equipment assigned to them so it's history will be know.

In any case, if the helmet is subject to a strong impact or if it displays any defects or cracks, it must be immediately replaced.

### SAFETY MARKING

The helmet includes the following markings:

Manufacturer's Trademark: Supertouch

Standard: EN 379:2012+A1:2012

Month and year of manufacture: See helmet shell

Notified Body: 2777

Certification mark: CE

Size: 53 - 65cm

Material: HDPE