



TEGERA® 256

Learn more

A SUPER SOFT CUT PROTECTION GLOVE

This comfortable glove has cut protection all around (level B). The thin split hide makes the glove super soft and suitable for all kinds of assembly work where high dexterity is desirable. Details like heat-resistant sewing thread and reinforced index finger contributes to the glove being extra durable.

CHARACTERISTICS

- High level of protection
- Extremely good fingertip sensitivity
- Extra flexible
- Perfect fit
- Extra comfortable
- Very durable
- Excellent grip

FUNCTIONS

- Withstands contact heat up to 100°C
- Reinforced index finger
- Reinforced seams
- Water and oil repellent

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 256

PREVENTS RISK OF

burn injuries, heat injuries, cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

cut risk environments, all-year use, warm environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

machine operating, building and construction, carpentry, installation work, electrical installation, hvac installation, sheet-metal work, engineering, transport work, machine driving, warehouse work, metalwork, welding, hot work, mining

PRIMARY INDUSTRIES OF USE

mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, building and construction, logistics

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE **All-round work gloves, Cut resistant gloves, Heat protection gloves**
CATEGORY **Cat. II**
PALM MATERIAL **Split hide**
THICKNESS **0,45-0,55 mm**
LINING **Fully lined**
LENGTH **215-275 mm**
COLOUR **Grey**
PAIRS PER: BUNDLE/CARTON **6/60**
DISPLAY TYPE **Thread**
CUT RESISTANCE (EN ISO 13997) **Cut resistance level B**
CUT RESISTANCE (EN ISO 13997) TDM: **7.7 N**
INNER MATERIAL SPECIFICATION **Para-aramid**
OUTER MATERIAL SPECIFICATION **Leather, Natural latex**

COMPLIANCE

CE Cat. II
TP TC 019:2011
Information/UIS
EN 407:2004 41314X
EN 388:2016 2322B
EN 420:2003 +A1:2009

FEATURES

Cut protection
Water repellent

SIZE	ARTICLE NUMBER	EAN
6	256-6	7340118322674
7	256-7	7340118322698
8	256-8	7340118322711
9	256-9	7340118322735
10	256-10	7340118322612
11	256-11	7340118322636
12	256-12	7340118322650

ejendals

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.