

# TECHNICAL SPECIFICATION



## Airfed Cobra™ Welding Grinding Visor Din 9-13

Airfed Cobra™ Welding Grinding Visor Din 9-13 / CBJ011-001-100



### DESCRIPTION

Airfed Cobra™ welding and grinding visor headtop for Jetstream®. The Airfed Cobra™ welding and grinding visor provides protection against impact and harmful light and has a uniquely developed highly efficient yet quiet air flow system through which 180 litres per minute of filtered air is delivered.

### OPTIONS

**Airfed Cobra™ Welding Grinding Visor Din 9-13  
(CBJ011-001-100)**

### SAFETY STANDARDS

EN 379 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 8 Jul 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Automatic Welding Filters  
Inactive DIN 4 (Deutsches Institut für Normung - German institute for Standardization), Active DIN 9-13 ADF. (Auto Darkening Filter)

Filter Reaction Time  
Light To Dark In 0.05ms.

ADF Power Supply  
Solar + Alkaline Battery



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)  
1



Protection from Liquid Splash  
3

Metal Free  
No

ADF Optical Class  
1/1/1/2 (Pure Optical Class, Light Diffusion Class, Luminous Transmittance Variation Class, Luminous Transmittance Angle Dependence Class.

Filter Clearing Time  
From Dark To Light : Minimum 0.1s Maximum 0.5s



Manufacturer's Trademark  
JSP Dagger



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.  
B





Resistance to Molten Metals and Hot Solids (optional)  
9

## RANGE

**Jetstream**  
ACCESSORIES

## DOWNLOADS

-  [Image Pack \(ZIP\)](#)
-  [doc-jetstream-welder-kit.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 8 Jul 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

