

KEY VAULTS

There are situations when additional security is needed and our key vaults are designed to meet that requirement. Designed to meet the highest standards of insurance companies our Key Vaults offer twice the strength and twice the reassurance of our standard key systems when controlling, tracking and securing keys to valuables and property.

KEY VAULT 48

- Heavy duty key cabinet designed to meet the growing need for added security
- 2.5mm fabricated steel cabinet with flush closing door to resist forced entry
- Locking by security deadlock with 5-pin Euro profile cylinder & 2 keys
- Adjustable colour coded and numbered hook bars allow the layout to be customised
- Ingenious key tabs are designed to hang so that the number is always visible
- Closed loops included for use with optional security seals
- Key locations can be recorded on the control index which is removable for added security
- Use your own cylinder to incorporate the cabinet into an existing suited system
- Cylinder can be easily changed in seconds to ensure total security
- Durable Light Grey paint finish will suit most environments

SKU: KV048



ADDITIONAL INFORMATION

Weight	8.000 kg
Dimensions	355 (H) x 300 (W) x 80 (D) mm
Standard	Silver
Capacity	48 keys
Locking Options	B - 3/4 Wheel Mechanical Combination, E - Mechanical Push Button Lock, G - Wittkopp Primor 2000, I - La Gard 702, L - Safe Logic

KEY VAULT FOR 48 KEYS IMAGES



Key Vault Interior



Euro Profile Cylinder



Security Seals & Loops



Key Vault 48 Push Button Combination Lock

KEY VAULT FOR 48 KEYS IMAGES



Key Vault 48 Push Button Combination Dead Lock



Key Vault 48 Push Button Combination Slam Lock



Key Vault 48 Dial Combination Lock



Key Vault 48 Electronic Lock REVO A

Your Securikey Stockist

Every effort has been made to ensure that the information in this brochure is correct. We have a policy of continually developing and improving our products and reserve the right to change specification without notice. By virtue of the Trades Description Act 1968 all measurements and weights must be considered approximate.

