

# Elite 22M Enclosed Festoon Sales Specification Sheet

## Description:

The Elite enclosed commercial range of festoon lighting comes in either 22M or 50M lengths with sealed for life ultrasonically welded light modules providing exceptionally water and dust protection. The 22M string comes with 10 modules delivering 560lumens per module, a total of 5600 lumens with a wide light distribution of 120°.

**Product Code:** LEDKITENC22

## Specification:

- 5600lm output
- Total power 80W, compared with 600W using conventional GLS variants.
- Compact and robust design
- CRI >80 and colour temperature of 6400K
- Fully CE compliant and manufactured to meet IP44.

## Differentiator:


- Low heat, no hot surfaces or additional guarding requirements.
- Low profile none-intrusive design, essential for limited access installations.
- Moulded fixing bosses to ensure quick and secure installation.
- All components are manufactured from robust materials to ensure the product performs in the harshest environments.

## Technical:

- Voltage – 110V 50/60Hz
- Plug – 110V 16A IEC60309
- Weight – 2.1kg
- Dims – 335 x 260 x 275mm (LxDxH)
- Power 80W
- Lumens 5600lm
- Light distribution - 120°



SMD LED



5600 LM



110Vac



IP54



Rough Service



-10°to +40°C