



Ultimate Industrial

HAND PROTECTION RANGE



TECHNICAL PRODUCT DATASHEET

CHEMICAL PROTECTION



UPDATED: 13/02/2019

LHD30

Medium duty black chemical resistant 13 inch gauntlet.

A 13" medium duty re-usable rubber gauntlet manufactured from a Natural Rubber and Neoprene compound for improved protection against abrasion and puncture. Chemically toughened to improve protection against many acids, alkalis, detergents and ketones. PowerGrip™ Honeycomb anti-slip embossed pattern creates a suction grip for excellent grip in a multitude of applications. Cotton flock lined for moisture absorption and added comfort.



FEATURES AND TECHNOLOGY



CHEMICAL PROTECTION



WATER REPELLENT



SUPERIOR GRIP



NITRO-DIAMOND GRIP



RUBBER

RUBBER



NEOPRENE

NEOPRENE

TYPICAL INDUSTRIES



MAINTENANCE



AGRICULTURE



FISHERY



FOOD PROCESSING



JANITORIAL

TECHNICAL INFORMATION

| | | |
|--------------------------|---|---------------|
| ORDER REF # | G/LHD30/BK | |
| COATING MATERIAL | N/A | |
| PACKING | PER PACK: 10 | PER CASE: 100 |
| SIZES AVAILABLE | 7-7.5 , 8-8.5 , 9-9.5 , 10-10.5 | |
| EU TYPE CERTIFICATION BY | SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, UK (Notified Body No. 0321) | |

CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)

EN388:2016



3 1 1 0 X

Abrasion (0-4)
Cut (0-5)
Tear (0-4)
Puncture (0-4)
TDM Cut (A-F)

EN ISO 374-1 :2016 /TYPE A



A K L M N P S T

EN ISO 374-5:2016



Protection against bacteria & fungi - **PASS**

Protection against viruses - **N/A**

0120

¹ 'X' denotes not tested.
² * Where applicable, EN388:2016 scores take precedent and are ongoing.
³ There is no correlation between coupe test levels and EN ISO 13997 / TDM cut test levels.



CAT III





Ultimate
Industrial

HAND PROTECTION RANGE



TECHNICAL PRODUCT DATASHEET

CHEMICAL PROTECTION



UPDATED: 13/02/2019

CERTIFICATION LEGENDS

EN388:2016



* For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

EN ISO 374-1 :2016 / TYPE □



| | |
|---|-------------------|
| A | Methanol |
| B | Acetone |
| C | Acetonitrile |
| D | Dichloromethane |
| E | Carbon Disulphide |
| F | Toluene |
| G | Diethylamine |
| H | Tetrahydrofuran |
| I | Ethyl Acetate |

EN ISO 374-5:2016



TYPE A - Gloves have achieved level 2 or greater against six of the chemicals listed in EN ISO 374-1 (below). The tested chemicals are identified by their code letters under the flask pictogram.

TYPE B - Achieved level 2 or greater against at least **three** of the chemicals.

TYPE C - Achieved at least a level 1 against **one** of the chemicals.

| | |
|---|--------------------------|
| J | n-Heptane |
| K | Sodium Hydroxide (40%) |
| L | Sulphuric Acid (96%) |
| M | Nitric Acid (65%) |
| N | Ammonium Hydroxide (25%) |
| O | Hydrogen Peroxide (30%) |
| P | Hydrogen Peroxide (30%) |
| S | Hydrofluoric Acid (40%) |
| T | Formaldehyde (37%) |

EN407:2004



EN511:2006



* For details regarding maximum permissible user exposure, see separate sheet.

¹ Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. ² 'X' denotes Not Tested. ³ Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between coupe test levels and ISO 13997 / TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational purposes only.

FURTHER INFORMATION

STORAGE / TRANSPORT: Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

PRECAUTIONS BEFORE USE: 1. Gloves should not be used when there is a risk of entanglement with moving machine parts. 2. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 3. The gloves should not come in contact with a naked flame or fire. 4. Do not subject to high speed or serrated blades. 5. Always read enclosed user instructions before using these gloves. 6. When used, protective gloves may provide less resistance to the dangerous chemicals due to changes in physical properties. 7. Movements, snagging, rubbing, de-gradation caused by the chemical contact etc. may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves. 9. This product has not been tested against viruses.

CONSTITUENTS / ALLERGIES: Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

FOOD TEST INFORMATION

Details of the suitability for contact with various food categories as detailed in EEC Directive are available on request. Please quote product reference when enquiring.

