

Provides sturdy coverage for demanding applications



FEATURES AND BENEFITS:

Exceptional Protection

The Microflex 93-843 offers an advanced barrier protection against contaminants due to its lower acceptable pinhole rates. Its 0.65 Acceptance Quality Limit for pinholes help set a new standard for protection.

Increased Productivity

Non-stick properties are built into the glove formulation to create a resistance to tape or adhesives, and to assist workers with improved efficiency and speed.

Secure and Confident Grip

Textured fingers ensure strong, efficient grip and maximum worker protection.

Effortless Donning and Doffing

Polymer coating assures easy donning to help protect workers in fast-paced environments.

Protection from Type 1 Allergies

Constructed without natural rubber latex materials or powder, to help protect from allergies, skin irritation and dryness.

Industries

- Automotive
- Chemical
- Laboratory
- Law Enforcement
- Food processing
- Manufacturing
- Pharmaceutical manufacturing
- Printing industry

Applications

- Crime scene evaluation
- Analytical testing
- Assembly and inspection
- Electronics
- Glass manufacturing
- Laboratory analysis and testing
- Light assembly tasks
- Maintaining equipment & instruments
- Paint and spray shops
- Preparing pharmaceutical products
- Protection from blood and other bodily fluids

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

	93-843
Material	Nitrile
Colour	Blue
Glove Design	Ambidextrous, Powder-Free, Chlorinated, Polymer Coated, Textured Fingers
Cuff	Beaded Cuff
Audit Standards	ISO 13485
Regulatory Compliance	PPED 89/686/EEC Category III, Complex Design, EN 455 1, 2 and 3, EN374-3, EN374-2 LEVEL 3 AQL .65, ASTM D6319, EN420 (sizing for special purposes), REACH Compliant, TGA, US QSR/FDA 510(K)
Packaging	100 gloves per dispenser, 10 dispensers per shipper carton, 1000 gloves per shipper carton.
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia

PHYSICAL PROPERTIES:

	TYPICAL VALUES					TESTING METHOD
	5.5 - 6	6.5 - 7	7.5 - 8	8.5 - 9	9.5 - 10	ASTM D3767/EN 420
Length (mm)	245	245	245	245	245	
Average Palm Width (mm)	75	86	98	108	115	

Freedom from Holes (Inspection level I)	0.65 AQL	ASTM D5151/EN 374-2
Palm Thickness Single Wall	0.11mm	ASTM D3767/EN 420

	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength	30 Mpa	30 Mpa	ASTM D 412-06a
Elongation at Break (%)	> 500	> 400	ASTM D 412-06a
Force at break (N)	10	11	EN 455-2

ORDERING INFORMATION:

	SIZE	5.5 - 6	6.5 - 7	7.5 - 8	8.5 - 9	9.5 - 10
93-843	REORDER NO.	93843060	93843070	93843080	93843090	93843100

* and ™ are trademarks owned by Ansell Limited or one of its affiliates. © 2014 All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

About Ansell

Ansell is a world leader in providing superior health and safety protection solutions that enhance human well-being. With operations in North America, Latin America/Caribbean, EMEA and Asia, Ansell employs nearly 14,000 people worldwide and holds leading positions in the personal protective equipment and medical gloves market, as well as in the sexual health and well-being category worldwide. Ansell operates in four main business segments: Medical, Industrial, Single Use and Sexual Wellness. Information on Ansell and its products can be found at www.ansell.eu.

For additional information visit us at www.ansell.eu, or call us at

Ansell Healthcare Europe

Riverside Business Park Block J Boulevard International 55, 1070 Brussels, Belgium
Tel. +32 (0) 2 528 74 00 Fax +32 (0) 2 528 74 01 E-mail info@ansell.eu

Ansell (UK) Ltd

30 - 32 Mariner Lichfield Road, Industrial Estate, Tamworth B79 7UL, United Kingdom
Fax: +44 (0) 1564 711 344 E-mail: info@uk.ansell.com



CE 0493



EN 374

EN 374