

PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PW25 - Ultra Vista Goggles Unvented

Collection: Goggles **Range:** Eye Protection

Materials: Polycarbonate, PVC, Nylon

Inner Pack: 12 Outer Carton: 144

Product information

Non-vented premium level goggles. Excellent protection against large dust particles, fine dust particles, gas and liquid splashes. Excelled when tested for high impact resistance and extreme temperatures (ranging from -5°C to +55°C). Can be worn with prescription glasses.

Eye Protection

PORTWEST eye protection range includes spectacles, safety goggles and visors, designed to protect the eyes and face of the workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.



EN 166 (1 BT 3 4 5 K N) EN 170 (2C-1.2)



Features

- · Single panoramic lens glasses
- \bullet Suitable for wearing over most prescription glasses
- Anti-scratch high level treatment coating, certified and marked with K on the lens
- \bullet Anti-fog high level treatment coating, certified and marked with N on the lens
- · Adjustable elastic headband for a perfect fit
- Protects from fluid and splashes
- 99% UV protection
- CE certified
- UKCA marked
- Individually packed for vending machines
- Retail bag which aids presentation for retail sales



PRODUCT SPECIFICATION & TECHNICAL DATASHEET

PW25 - Ultra Vista Goggles Unvented Commodity Code: 9004901000

Test House

BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797)

John M. Keynesplein 9 , The Netherlands Cert No: CE 716472

BSI Assurance UK Ltd (Notified Body No.: AB: 0086)

The British Standards Institution MK5 8PP, United Kingdom Cert No: UKCA 767378

Carton Dimensions/Weight

| Item | Colour | Len | Wid | Hgt | Weight(Kg) | Cubic(m³) | EAN13 | DUN14 |
|---------|--------|------|------|------|------------|-----------|---------------|----------------|
| PW25CLR | Clear | 63.0 | 43.0 | 40.0 | 0.1250 | 0.1084 | 5036108258963 | 15036108748195 |