

## PA900 Series Technical Specifications: PA922EU

PA922EU – Hard Hat with Standard Shroud	
Attribute	Specification
Approval Standard	EN 12941:1998 + A1:2003 + A2:2008
Approved for Use with	Honeywell North PA500EU Series PAPR; Honeywell North PA700EU Series PAPR
Classification	TH3
Eye & Face Protection	EN166 1.BT.9.N
Head Protection	EN 397+A1
NPF (EN 12941)	NPF500
Visor Material	Coated Polycarbonate, Anti-Scratch, Anti-Fog
Faceseal or Shroud	Shroud, Standard
Shroud Material	Polyester Blend
Shroud Care	Washable by Hand or laundered in warm water (75° C)
Visor Area	200 cm <sup>2</sup>
Visor Thickness	2 mm
Size Range (Circumference)	6 1/2- 8 in. / 52-64 cm
Headgear Shell	ABS
Headband	Polyamide Velour Fabric
Visor Frame	EN 166 3.9.BT
Hearing Compatibility	VS110M - SKU 1035185-VS VS130M – SKU 1035188-VS
Operating Temperature	-10°C – +50°C / 10°F to 122°F in 20-90% RH
Storage Temperature	-30°C – +55°C / -22°F to 131°F in 90% RH
Natural Rubber / Latex Content	No
Weight g/lb. (complete assembly)	1340g / 2.95LB
Shelf-life	Maximum shelf life is 4 years if properly maintained and kept in its original, dry and undamaged packaging in storing temperatures -30°C – +55°C up to 90% humidity