

PRODUCT DATA

3478 LeakSeal®

DESCRIPTION

Rust-Oleum® LeakSeal® is an easy to use, rubberized protective utility coating designed to fill and seal leaks and cracks.

MAIN PROPERTIES

Provides a water-tight, flexible seal that prevents moisture penetration and corrosion - dries to a semi smooth finish - will not sag or drip - can be top-coated with latex or oil-based paints.

RECOMMENDED USES

Designed to fill and seal leaks and cracks on metal, aluminium, galvanized metal, PVC, concrete, masonry, asphalt/bituminous roofing materials, vinyl siding, fiberglass, and more.

TECHNICAL DATA

Appearance: Semi smooth
Colour: Black, white, transparent and aluminium

Drying times 20°C/50% r.h.
To touch: 20 - 30 minutes
To handle: 45 - 60 minutes
To recoat: Apply second layer LeakSeal after 15 - 30 minutes
Top-coated with water-based or oil-based paints after 24 hours.
Full hardness: 24 hours

Coverage

Theoretical: 0,74 m² per aerosol at 65 µm dry film thickness
Practical: Practical coverage depends on many factors such as porosity and roughness of the substrate, size of the leakage and material losses during application.

SURFACE PREPARATION

Remove all dirt and debris from the area to be coated. Wash area with a detergent and water solution, rinse with fresh water, and allow the surface to dry thoroughly. Remove any loose paint or previous coatings with a wire brush or sandpaper. Lightly sand glossy surfaces. Wipe the sanded surface clean when finished.

Test previous coated material for compatibility before use.

DIRECTION FOR USE

Shake aerosol vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum for technical support. A test spray on cardboard is recommended to obtain feel for the spray pattern. Hold the aerosol 8-18" (20 - 45 centimetre) from the surface and spray in short even strokes. It is recommended to apply a light first coat. Apply a second heavier coat to ensure proper coverage. A thicker film can be achieved by moving the nozzle closer to the surface. Initial spray may have some foaming or bubbling, but will dissipate as the coating dries. For best results, apply 2 coats. Allow to dry 15-30 minutes between coats.

REMARKS

- If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.
- Wipe off tip when finished.
- Clean-up wet paint with xylene or mineral spirits. Properly discard empty container.
- Do not burn or place in home trash compactor.

PRODUCT DATA

3478 LeakSeal®

APPLICATION CONDITIONS

Use outdoors or in a well-ventilated area such as an open garage. Apply when temperature is between 50°F and 90°F (10 - 32°C) and humidity is below 85% to ensure proper drying.

Do not apply to surfaces, when heated, exceed 200°F (93°C).

Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.