

PS47 - Endurance HV Clip-On Ear Protector

Collection: Ear Muffs

Range: PPE

Materials: ABS, Polystyrene

Product information

High-Visibility colour. This product is compatible with Endurance Helmets, Height Endurance Helmets, Peak View Helmets and the PS51 Helmet. Warning: attenuation performances vary depending on the helmet style they are used with.

AS/NZS 1270 (SLC(80) 22dB - Class 4)

EN 352-3

ANSI S3.19 (NRR 24dB)

Ear Muffs

Portwest Hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colours for earmuffs allow a personalised choice. An updated range of earplugs complete our competitive and performing offer.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Features

- CE-CAT III
- Easy to clip-on
- Hi-Visibility colour for visibility in daylight
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines



	Range
Hi-Vis Orange	-
Hi-Vis Yellow	-

PORTWEST®

PRODUCT SPECIFICATION & TECHNICAL DATA

PS47 - Endurance HV Clip-On Ear Protector

Commodity Code: 6506101000

Test House

ALIENOR CERTIFICATION (Notified Body No.: 2754)

ZA du Sanital

86100 , France

Cert No: 2754/1246/159/06/18/0330

CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m ³)	EAN13	DUN14
PS47YER	Yellow	50.0	47.0	52.0	0.2800	0.1222	5036108276110	15036108766205

PORTWEST®

PRODUCT SPECIFICATION & TECHNICAL DATA

PERFORMANCES - SOUND ATTENUATION

PW47/ PS47 + ENDURANCE SAFETY HELMETS (PS54/PS55/PW54/PW55) & + ENDURANCE HEIGHT SAFETY HELMETS (PS53)

PW47/PS47								
A Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
B Mean Attenuation (dB)	13.4	12	20.1	28.9	32.4	32.5	33.6	33.1
C Standard Deviation (dB)	5.8	6.7	4.1	5.0	5.4	4.4	6.3	6.9
D Assumed Protection (dB)	7.6	5.3	16.0	23.9	27.1	28.1	27.2	26.2
SNR 25dB H:28dB M: 23dB L: 14dB								

PW47/ PS47 + PEAK VIEW HELMETS (PV50/PV54/PV60/PV64)

PW47/PS47								
A Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
B Mean Attenuation (dB)	12.9	12.6	20.8	31.8	35.3	34.3	33.5	36.0
C Standard Deviation (dB)	5.9	5.3	3.7	5.0	2.9	5	7.8	7.8
D Assumed Protection (dB)	7.0	7.3	17.1	26.8	32.4	29.3	25.7	28.3
SNR 27dB H:29dB M: 25dB L: 16dB								

PW47/ PS47 + WORKBASE SAFETY HELMETS (PS51)

PW47/PS47								
A Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
B Mean Attenuation (dB)	12.1	11.7	19.5	28.8	32.8	34	31.3	30.8
C Standard Deviation (dB)	4.4	5.0	5.1	6.8	6.0	4.4	7.9	8.6
D Assumed Protection (dB)	7.7	6.6	14.4	22.1	26.8	29.6	23.4	22.2
SNR 24dB H:26dB M: 23dB L: 15dB								

PERFORMANCES - SOUND ATTENUATION- ANSI S.19-1974

PW47/ PS47 + ENDURANCE SAFETY HELMETS (PS54/PS55/PW54/PW55) & + ENDURANCE HEIGHT SAFETY HELMETS (PS53)

Tested by Michael & Associates, Inc. – 400 Long Lane, PA Furnace, PA 16865, USA

PW47/PS47									
NRR (NOISE REDUCTION RATING) = 24dB									
A Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
B Mean Attenuation (dB)	16.9	20.5	28.1	37.0	37.0	37.0	35.1	32.4	35.3
C Standard Deviation (dB)	2.7	2.1	3.0	2.8	2.7	3.1	1.8	2.6	3.2

PS47YER