

### PV50 - Peak View Hard Hat Vented

**Collection:** Head Protection

**Range:** PPE

**Materials:** 100% Polycarbonate

**Outer Carton:** 20

#### Product information

Portwest exclusive design and Patented Model. Translucent shell to see through peak and sides: allows the wearer to look upwards without the need to tilt the head. Extra strong yet ultra lightweight Polycarbonate shell, offering UV rays protection. 6 points textile harness, adjustable size. Vented shell for extra air-flow.

#### Head Protection

PW rapidly expanding head protection product range aims to benefit our customers by combining the most updated styles and standards in head protection, irrespective of job or location. A wide selection of compatible accessories is also available. A full explanation of features and performances are given in order to help you make a more informed choice.

#### PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

#### Standards

EN 397 (-20°C)

ANSI/ISEA Z89.1 TYPE II (Class C)



#### Features

- CE certified
- Portwest exclusive design and patented model
- Translucent shell to see through peak and sides
- Extra strong yet ultra light weight Polycarbonate shell
- Vented hard hat allowing a refreshing airflow around the head
- UV 400 stabilised
- 6 points textile harness
- Buckle size adjustment for easy fitting
- Soft foam sweat band included
- Compatible accessories available

#### Colours

	Range
Smoke	-
Blue	-
Clear	-
Yellow	-
Green	-
Red	-
Orange	-
Pink	-

# PORTWEST®

## PRODUCT SPECIFICATION & TECHNICAL DATA

### PV50 - Peak View Hard Hat Vented

Commodity Code: 6506101000

#### Test House

SAI Global Assurance Services Limited (Notified Body No.: 2056)

Winterhill House, Snowdon Drive

MK6 1AX, UK

Cert No: CEC40211

#### CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m <sup>3</sup> )	EAN13	DUN14
PV50CLR	Clear	59.0	47.0	38.0	0.4100	0.1054	5036108266371	15036108756046