

3AA

INTRINSICALLY SAFE INTRANT™ DUAL-LIGHT ANGLE LIGHT

XPP-5566RX/GX

NIGHTSTICK®
Life Depends on Light™

45°

EXCLUSIVE
DOWNWARD FLOODLIGHT

HEAD ROTATES 90°

**DUAL
LIGHT
TECHNOLOGY**



Head rotates 90° – directing beam exactly where it's needed most



45° downward floodlight lights an 8 foot walking area



Easy-to-use with gloves, the large switches **independently control** separate LEDs



Heavy-duty, clip and V-ring **securely holds tight to gear** in any situation



205 LUMENS

AVAILABLE IN HI-VIZ GREEN.

INTRANT®**DUAL-LIGHT™ ANGLE LIGHT****3AA****ITEM NUMBER/UPC**

XPP-5566RX (Red), 0 17398 80629 9
 XPP-5566GX (Green), 0 17398 80628 2

MARKET APPLICATIONS

Hazardous work environments, fire, rescue, industrial and automotive

CERTIFICATIONS

- CE, cULus, ATEX, IECEx, UKCA, InMetro, NFPA

CASE MATERIAL

- Glass filled nylon polymer

LUMENS/RUNTIME**FLASHLIGHT**

- HIGH: 200L, 11 hrs. runtime
- MEDIUM: 110L, 18 hrs. runtime
- LOW: 60L, 33 hrs. runtime
- STROBE

FLOODLIGHT

- HIGH: 100L, 11 hrs. runtime
- MEDIUM: 40L, 18 hrs. runtime
- SURVIVAL: 20L, 33 hrs. runtime

DUAL-LIGHT

- 205L, 11 hrs. runtime

CANDELA**FLASHLIGHT**

- HIGH: 40,256
- MEDIUM: 15,625
- LOW: 8,750

BEAM DISTANCE**FLASHLIGHT**

- HIGH: 401m
- MEDIUM: 250m
- LOW: 187m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.6 in (168mm)
- WIDTH: 2.6 in (66mm)
- DEPTH: 2.6 in (66mm)
- HEAD DIAMETER: 2.1 in (53mm)
- WEIGHT: 11.1 oz (315g)(with batteries)

BATTERY

- 3AA batteries (included)

WARRANTY

- Limited Lifetime Warranty

WHAT'S INCLUDED

- Angle light
- AA battery carrier
- 3AA batteries
- Instruction manual

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	200 LUMENS	60 LUMENS	205 LUMENS
	11h	33h	11h
	401m		
	40256cd		
			
			

Bayco Products, Inc. XPP-5566RX
 640 S. Sanden Blvd., Wylie, TX 75096

Ex is FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
 For use with Bayco Li-Ion Battery Pack 5566-BATT or
 5566-CARRIER with 3 AA Energizer Type EN91 or E91
 batteries only

ATENÇÃO - UTILIZAR SOMENTE BATERIAS ENERGIZER E91 OU EN91
 ATENÇÃO - NÃO SUBSTITUIR A BATERIA QUANDO UMA ATMOSFERA
 EXPLOSIVA ESTIVER PRESENTE
 ATENÇÃO - NÃO RECARREGUE A BATERIA EM ÁREA CLASSIFICADA.

CLASS I DIV 1 GRPS A-D T4
 CLASS II & III DIV1 GRPS E-G T135°C
 CLASS I ZONE 0 Ex ia IIC T4 Ga
 M1 Ex ia op is I Ma
 II 1 G Ex ia op is IIC T4 Ga

Ex ia op is I Ma
 Ex ia op is IIC T4 Ga
 DEMO 17 ATEX 1927
 UL220EX2428
 IECEx UL 17 0082
 -20°C to Tamb to +40°C
 1.5V/Cell Alkaline
 3.7V/Cell Li-Ion
 IP-67
 Use: 10y

Control Drawing: 5566-CERT-DWG-1-03
 SEE INSTRUCTION MANUAL
 VOIR MANUEL

For Battery Charger Connection see Instruction
 Manual Drawing: 5562-68-MECH-DWG-1-09
 MFG MM-YY

