



310 ORANGE

ORIGINAL ORANGE LATEX GRIP GLOVE

Flexible and robust offering great dexterity, outstanding grip and good resistance to tearing, ideal for heavy duty manual handling.

FEATURES

- › A flexible, robust glove offering great dexterity and with good resistance to tearing
- › Breathable back of hand to reduce perspiration
- › Surface provides tactile feel and better grip
- › Greater hygiene
- › Designed for easy movement and continuous wear
- › No irritation by seams in contact with the skin



SUITABLE FOR

Typical Industries

- Construction
- Highway Maintenance
- Logistics
- Municipal Services
- Heavy Engineering

Suitable Applications

- Bricklaying
- Maintenance
- Manual Handling
- Refuse Collection
- Tiling

CERTIFICATION

CAT II



EN 388:2016



2142X

See overleaf for explanation





310 ORANGE

PRODUCT INFORMATION

MATERIALS	LINER:	10 gauge cotton
	COATING:	Natural Latex
COLOUR	Yellow/orange	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
8/M	SHO310Y2	10 pairs per bag
9/L	SHO310Y3	120 pairs per case
10/XL	SHO310Y4	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use
- **WARNING:** Latex may cause allergies

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter