



HIGH VISIBILITY, LATEX GRIP GLOVE FOR INTENSE MANUAL HANDLING

Durable latex coating to the palm provides good mechanical resistance. Phosphorescent markings on a highly visible liner aid safety in poorly-lit environments.

FEATURES

- › Fluorescent yellow with an orange palm coating for increased visibility in low light
- › Natural rubber latex palm coating
- › Rough finish over surface of palm
- › Seamless 10 gauge liner
- › Breathable back of hand and fingers
- › Designed for easy movement and continuous wear
- › Unique SHOWA ergonomic shape that replicates the natural curve of the human hand reducing hand fatigue
- › Exceptional grip, dexterity and durability



VENDING
MACHINE
COMPATIBLE



SUITABLE FOR

Typical Industries

- Construction
- Logistics
- Municipal Services
- Railways
- Transport

Suitable Applications

- Aircraft Hold Handling
- Demolition
- FOD Prevention
- Hand Signalling
- Highway Maintenance
- Manual Handling
- Road and Railside Construction

CERTIFICATION

CAT II



EN 388:2016



2142X

See overleaf for explanation



317

PRODUCT INFORMATION

MATERIALS	LINER:	10 gauge polyester
	COATING:	Natural Latex
COLOUR	Yellow/orange	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- USE: General handling glove. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use
- WARNING: Latex may cause allergies

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S	SHO3171	10 pairs per pack 120 pairs per case
8/M	SHO3172	
9/L	SHO3173	
10/XL	SHO3174	

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance		Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

