# **TECHNICAL DATA**







Lubricants



360° Spray System for all angle use



NSF Registered: category H1, no. 161243





Halal Certified Product: AN001183

## **MOISTURE REMOVER FG**

#### **CORROSION PROTECTION AND LUBRICATION**

Moisture Remover FG prevents rust and corrosion on all ferrous and non-ferrous metals during storage, production and transport. Displaces and seals out moisture, especially after washing equipment. Penetrates through corrosion to loosen seized parts and lubricates without leaving a sticky residue. Cleans light soils and contaminants. Non-drying protective film prevents 'fingerprinting'.

### **PRODUCT CODES / FILL SIZES**



- APPLICATIONS
- Materials & equipment storage
- Post wash-down treatment
- Machined surfaces
- Corrosion protection
- Light lubrication

#### DIRECTIONS

- To displace moisture, spray damp/wet surfaces until run-off is clear and moisture-free.
- Apply liberally and allow to penetrate to free rusted parts. Full penetration may require several hours.
- Moisture Remover FG can be removed with solvent based cleaners such as Industrial Degreaser FG or with aqueous cleaners such as Aquasafe FG.
- Do not use on energised equipment. Use in a well ventilated area.





#### **TECHNICAL DATA (WITHOUT PROPELLANT)**

Appearance	Clear
Specific Gravity (@ 20°C)	0.83
Freezing Point	-10°C
Flash Point (open cup)	78°C
Ultimate Film Thickness	2 x 10⁻⁵m (@ 20°C, after a 24 hr spread)
Maximum Expected Coverage	100 m2/I. (@ 20°C, after a 24 hr spread)
Solvent Dissipation (@ 20°C, thin film)	2-4 h
Film Properties (after evaporation of solvent)	
Dynamic Viscosity (@ 20°C)	64 mPa.s
Falex True Load Failure	8900 N (ASTM D 3233, Proc.A)
Salt Spray Resistance	65 h
Heat Resistance	120°C (150°C short time)

#### MATERIALS COMPATIBILITY

 OK
 Compatible with most painted surfaces, coatings, plastics and rubbers

 CAUTION

 NOT OK

#### **STORAGE & SHELF LIFE**

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

#### **MISREPRESENTATION ACT 1967**

#### TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 4.0 Created: July 2019 Updated: June 2021



ISO 9001 Quality Management