

## TECHNICAL SPECIFICATION/PRODUCT DATASHEET



<b>PRODUCT CODE</b>	CD 458 ENB
<b>SUB-CATEGORY</b>	Solid top
<b>MATERIAL</b>	Nylon composite (100 % Recyclable)
<b>BASIC DIMENSIONS</b>	Clear opening: 450 Diameter Overall size: 544 Diameter Overall Depth: 122 Frame Depth: 51 Depth of insertion: 25
<b>WEIGHT (Kgs)</b>	9 Kgs
<b>LOAD RATING CLASSIFICATION</b>	B125
<b>LOAD TEST DATA</b>	Tested to BS EN 124-1:2015 Clauses 4.1,4.2,6.2,6.3,6.4, 6.5,6.6,6.7,6.10,6.13,6.15,6.16,7.1,7.2 and 7.3 BSI Direct test - Test report No. 3484675



## TECHNICAL SPECIFICATION/PRODUCT DATASHEET

### KEY FEATURES

B125 Loading capability, lighter than equivalent ductile product.

Perfect partner for CD U455 chamber riser.

Fits other manufacturer's 450 PPIC chamber (depending on exact size).

Aesthetically pleasing, will not rust/"bleed" onto the surround.

Unique slip-resistant surface tread pattern.

Dual locking (lid locks to frame + frame locks to chamber)

Compatible with reducer (available separately) to restrict access into deep chambers as per Part H of the building regulations.

Made from 100 % recycled material

Made in Britain

