



MAXIMIZING THE POTENTIAL OF THE EXPONENTIAL UPGRADE.

ZENITH X MAX CE

STANDARD
EN 397 | 440V a.c. / -30°C / LD / MM
EN 50365 (Class 0)
CE 2008

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral
impact, 4.2.1.4 rear impact
4.2.2 | Penetration

CATEGORY
III

MATERIAL
EXTERNAL SHELL:
HD Polypropylene

INTERNAL SHELL:
Neopor® Cycled® by BASF | EPS
obtained from chemical recycling of
plastic waste.

HEADBAND:
Soft PA Nylon

TEMPERATURE OF USE
-30°C / +50°C

WEIGHT
570 g

SIZE
Adjustable – from 60 to 66 cm



WHE00130

○ 201	● 205	● 210
● 202	● 206	● 215
● 203	● 208	
● 204	● 209	

TECHNOLOGIES

- **D-CORE TECHNOLOGY** Low-density Neopor® Cycled® EPS core protects from top impacts.
- **HD CROWN PROTECTION** High-density Neopor® Cycled® EPS inner shell protection designed for all-around impacts.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- **DRY+ LINER** Moisture-wicking fabric for enhanced comfort.
- **ADAPTIVE FIT SYSTEM** Size adjustment system that adapts to create a personalized, secure fit.
- **ADVANCED CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- **COLOR-CODED FASTENER** The color of the fastener indicates the EN standard to which the chinstrap refers.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.

3
YEARS
GUARANTEE

10
YEARS
LIFE SPAN



SCAN FOR
COMPLETE
COLLECTION